

SMG Gold

Semi-Synthetic Grease – EP2

Description

SMG Gold is truly a heavy-duty multipurpose EP grease designed for low or high speed plain and rolling element bearings, and sliding mechanisms operating under generally difficult conditions such as found in steel mills, manufacturing plants and automotive applications. Special additive technology and highly refined petroleum oils gives high film strength under EP conditions with good oxidative and thermal stability. Specially designed component mixture provides high dropping point, mechanical and thermal stability with heavy water and corrosion resistance. SMG Gold has exceptional resistance to water wash and extremely low oil bleed characteristics which insures protection at high temperatures and high radial forces.

Applications

SMG Gold grease is ideal where hot and cold, low and high-speed bearings must share the same lubricant. Designed for wet and hot end use for roll neck journal bearings found in Paper & Steel Mill operations. Excellent for heavily loaded hinge pins, splines, couplings, CV and universal joints. Use on rolling mills, slabbing mills, truck chassis, wheel bearings; also general lube points on track rolls of heavy duty construction and earth moving equipment. This grease can withstand higher speeds and higher constant temperatures than our other multipurpose greases.

Features and Benefits

- **Increased Production**: Increased parts life reduces downtime for repairs or parts replacement coupled with decreased labor to repair those parts. Increased production increases **REVENUES**.
- Excellent Corrosion Protection: **SMG Gold** provides long life in corrosive environments.
- Resistance to Water: These greases are insoluble in water
- High Extreme Pressure Properties: They will carry heavy loads due to inherent EP properties.
- Excellent Shear Stability: Will not thin down due to heat or shear, even with heavy water wash.
- Excellent Thermal Stability: May be used to 572°F with proper re-lubrication cycles.

Extreme Industrial Lubricants, Inc.

26873 Sierra Hwy, Suite 133 || Santa Clarita CA, 91321 USA Tel: 661-298-8510 Web Site: www.extremelubricants.com

The product information and specifications contained here in have been compiled for the convenience of the user. It is intended to be used by people with technical skills. Extreme Industrial Lubricants disclaims any warranty, expressed or implied, of merchantability. Whenever the information herein is to be used for a critical application, it should be verified independently. This information is not intended as a license to operate under, or a recommendation to infringe any patent.



EXTREME INDUSTRIAL LUBRICANTS, INC.

Santa Clarita CA, 91321

TECHNICAL DATA – SMG GOLD GREASE

(Not For Specification Purposes)

Typical Physical Properties for SMG Gold Grease				
Property	Test Method	Units	SMG Gold #2	
Color & Texture	Visual		Brown	
Kinematic Viscosity of Base Oils @ 40 ° C	ASTM D 445	cSt (SUS)	118	
Worked Penetration, 60 Strokes @ 25°C	ASTM D-217	mm/10	280	
Mechanical Stability	ASTM D-217 % change from P60	P 100.000 Strokes P 10,000 Strokes w/	2.4 %	

Shell Roll Stability	ASTM D-1831	% change from P60	3.2 %
Timken OK Load	ASTM D-2509	lbs. / kg.	80/36
4-Ball EP Weld Load LWI	ASTM D-2596	Kgf.	620 kg. 80
4 Ball Wear, Scar Dia. (40kg., Load, 1200 RPM, 75°C, 1-hr.)	ASTM D-2266	Average Wear Scar in mm	0.38 mm
Dropping Point	ASTM D 2265	°F	594
Rust Test Copper Corrosion Salt Fog Spray	ASTM D-1743 ASTM D-130 ASTM B-117	Rating Classification Hours to Failure	Pass 1b >1000 hrs.
Water Washout	ASTM D-1264, @ 80 ° C	% Loss	1%
Oxidation Bearing Life Rotary Bomb Oxidation	ASTM D-3527 ASTM D-942	Hrs. PSI drop, 500 hrs.	200 6.0 lbs.

Subject to Usual Manufacturing Tolerances

Extreme Industrial Lubricants, Inc.

26873 Sierra Hwy, Suite 133 || Santa Clarita CA, 91321 USA Tel: 661-298-8510

Web Site: www.extremelubricants.com

The product information and specifications contained here in have been compiled for the convenience of the user. It is intended to be used by people with technical skills. Extreme Industrial Lubricants disclaims any warranty, expressed or implied, of merchantability. Whenever the information herein is to be used for a critical application, it should be verified independently. This information is not intended as a license to operate under, or a recommendation to infringe any patent.

