XLERATOReco® HAND DRYER



ENHANCED STANDARD FEATURES



Adjustable Speed and Sound Control



Multi-Voltage Options: 110-120V Or 208-277V



500 Watts No Heat



Externally Visible Service LED

10 SECONDS¹ 95%
COST SAVINGS
versus paper towels

1.7
WATT HOURS







MODELS: XL - BW W GR C SB SI SP - ECO -H (HEPA Filter) OPTIONS: -1.1N (Noise Reduction Nozzle) -VOLTAGE (See Chart)

EXCEL



XL-BW-ECO White Thermoset Resin (BMC)



DRY TIME: 10 SECONDS¹

ENERGY PER USE: 1.7 Wh¹



UL Environment published the first global Product Category Rules (PCR) for hand dryers which outlined industry consensus testing procedures to quantify environmental impact and performance. Third-party testing to these guidelines documents a product's environmental impact over its lifecycle. This impact is detailed in certified, internationally-recognized Environmental Product Declarations (EPDs). EPDs enable specifiers and buyers to make true apples-to-apples comparisons and more informed product selections. Excel Dryer received the industry's first certified EPDs.

FEATURES & BENEFITS

Electrostatic HEPA Filtration System: Removes 99.999% of viruses and 99.97% of potentially present bacteria² at 0.3 microns from the airstream.

- 50% Longer Life
- Industry Leading 7-Year Limited Warranty
- 95% Cost Savings Vs. Paper Towels
 - Helps Qualify For The Most LEED® Credits
- ✓ No Heat Technology
- ✓ Made In USA Certified®
- A Hygienic Hand Drying Solution
- ✓ Washable Pre-Filter

OPTIONS

✓

1.1" Noise Reduction Nozzle: Reduces the sound level by 9 decibels by significantly decreasing air deflection noise while only increasing dry time by approximately 3 seconds.



XL-W-ECO White Epoxy Painted



XL-GR-ECOGraphite Textured
Painted



XL-SP-ECO⁴
Custom Special Paint



XL-SI-ECO⁵ Custom Special Image



XL-C-ECO Chrome Plated



XL-SB-ECO Brushed Stainless

PERFORMANCE

ADJUSTABLE SOUND LEVEL: 65-75 dB ADJUSTABLE VELOCITY: 13,000-20,000 LFM FLOW RATE: 43-65 CFM

DIMENSIONS

Width 11 ³/₄" (298 mm) **Height** 12 ¹¹/₁₆" (322 mm) **Depth** 6 ¹¹/₁₆" (170 mm)

ELECTRICAL

VOLTS	AMPS	WATTS	HERTZ	
110-120V	4.3-4.5A	460-530W	50/60 Hz	c (U) us
208-277V	2-2.2A	425-500W	50/60 Hz	c(UL)us
230V	2.2A	500W	50 Hz	Œ

NOTE: Drawing 4.5 Amps or less allows for the installation of multiple XLERATOReco units on one circuit, significantly reducing installation costs and creating a return on investment of less than one year.

CERTIFICATIONS











Building Green

RoHS



WEIGHT

XL-BW-ECO: 15 lbs. (6.8 kgs.) XL-SB-ECO: 16 lbs. (7.26 kgs.) XL-W-ECO, XL-GR-ECO, XL-C-ECO, XL-SI-ECO, XL-SP-ECO: 17 lbs. (7.71 kgs.)

ACTIVATION MOUNTING

Automatic Sensor Operated Surface Mounted

SUGGESTED MOUNTING HEIGHTS

Men 45" (114 cm) **Women** 43" (109 cm) **Accessible** 37" (94 cm) Note: Heights measured from floor to bottom of dryer.

ACCESSORIES

Antimicrobial Wall Guards (#89B, #89W, #89S)

XChanger® Paper Towel Dispenser Retrofit Kit (#40575, #40550)

ADA-Compliant Recess Kit (#40502)



¹Dry time and energy use testing performed by SGS International on standard XLERATOR Hand Dryer with 0.8" nozzle to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers.
²Based on testing performed by LMS Technologies, 2020. ²LMS Technologies, 2014. ⁴Special Paint powder-coated covers are available in many colors and textures. ⁵Exclusive digital image technology allows for the addition of company, school or team logos with any color, design or a "green message".



