



# MU408a

COLUMN SERIES | Two Way Full Range Column Speaker

## Product Description:

MU408 installed line array column loudspeakers are used in applications including sound reinforcement for Houses of Worship, Event, Theme Parks, Transit Terminals and shopping malls etc. The T series delivers extraordinary performance where high speech recognition and natural sounding music is required at unmatched value.

## Key Features and Benefits:

- Vertical line array of 8x4" LF driver
- 44mm compression driver loaded with wave guide
- Frequency response 80Hz-18kHz(-3dB)
- Sensitivity 92dB, Max SPL 116dB
- 150x30 degree controlled coverage pattern
- Birch plywood construction
- Durable Polyurethane textured base paint
- Quick install U bracket included with multiple mounting points provided
- Designed for high speed recognition and natural sounding music
- Optional MU408 hanging hardware



## System specification:

Construction	15mm birch plywood
Transducers	1 x 44mm HF, 8 x 4" LF
Frequency Response (-3dB)	80-18kHz
Rated Power	240W (RMS)
Dispersion(HxV)	150° x 30°
Sensitivity (1W@1m)	94dB
Maximum SPL	116dB/122dB (Peak)
Rated impedance	8Ω
Crossover	2kHz
Hanging points	6 x M8
Connector	4-screw terminal
Dimension (W x H x D)	164 x 1138 x 233mm
Package dimension (W x H x D)	305 x 1240 x 243mm
Net Weight (1 piece/pack)	16.7kg
Gross Weight (1 piece/pack)	18.2kg

