

S1200B

12" LF Speaker

DESCRIPTION

Professional portable and installed plastic loudspeakers where high sound quality is required. Can be used in applications including sound reinforcement in Front of House and Foldback applications in Houses of Worship, Events, Clubs, Rehearsal Halls etc. The S Series is suitable for music and vocal reproduction in demanding applications.



FEATURES

- High output SPL and sensitivity
- 2 x 12" high power transducers
- Injection molded
- 2 x NL4 connector
- Cabinet design for FOH use
- Suitable for use to augment the main system
- Portable system (stand), or permanent installation (wall, ceiling)
- Powder coated grill with foam backing
- Available in black or white

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	50Hz-1.8kHz
	Max SPL @ 1m:	128dB/134dB(PEAK)
Transducers	Woofers:	2 x 12" LF
Input/Output section	Input Connectors:	2 x NL4
	Sensitivity (1W @ 1m):	99dB
Processor section	Crossover frequencies:	<250Hz
Power section	Total Power:	800W(RMS); 1600W(MUSIC); 3200W(PEAK);
	Nominal Impedance (Ohm):	4Ω
Physical specifications	Cabinet/Case Material:	Polypropylene Cabinet, ABS baffle, metal grille
	Handles:	1 x Plastic Handles
	Grille:	Powder Coated Steel with Grille Cloth
	Color:	Black
Size	Dimension (W x D x H):	416 x 423 x 721mm / (16.4 x 16.7 x 28.4in)
	Package Dimensions (W x D x H):	485 x 485 x 792mm / (19.1 x 19.1 x 31.2in)
Weight	Net Weight:	24.5 kg / 54 lb
	Gross Weight:	28 kg / 61.7 lb