HARDWARESOURCE HINGE SKU 268706

Salice Silentia Hinge For Frameless Inset Cabinets REVEAL TABLES

WHAT IS A REVEAL?	When a door swings, it needs a certain amount of clearance at both ends of the door so that anything close (ie. another door or a side panel) does not interfere with the opening door. This clearance gap is called the reveal. The table below shows the minimum amount of reveal		
	needed for this hinge.	3mm	
		4mm	
	The minimum reveal is very important for inset doors. For inset doors,	5mm	
FOR INSET	the reveal is the gap between the edge of the door and the side panel or the edge of the face frame.		
DOORS			
	(energy)	7mm	
	The first table below shows the reveal between the door and cabinet	8mm	
	side wall based on bore distance and mounting plate height. The bore distance is the distance from the edge of the door to the edge of the cup that is drilled in the back of the door. See "B" on the chart to the right for further clarification. When doing replacements, measure and match your existing reveal distance and brea distance to verify if this	9mm	
		9.5mm	
		10mm	
		11mm	
	hinge and plate will work for you. Note that this chart has a range listed due to the hinge being adjustable -1.5mm and +4.5mm.		
HOW TO		13mm	
USE THESE CHARTS	The second table below shows the minimum amount of reveal required for this hinge depending on bore distance and door thickness. For new		
	installations, a 3mm bore distance is highly reccomended to give you	14mm	
	the most amount of adjustment. B = Bore Distance C = Cup Centerpoint	15mm	
	Example: If you want a 2.5mm reveal, you would use the first chart verify how large of a		
	bore distance is required. In this case it would be 5mm. You would then use the second table to determine how thick of a door will allow this reveal. Using your previously acquired bore		
	distance (5mm), you can now determine that a door between 16mm and 19mm thick will allow a 2.5mm reveal. If you need to use a thicker door, you would need to increase your reveal by decreasing your bore distance.		
			decreasing your pore distance.

		BORE DISTANCE			
		Змм	4мм	5мм	6мм
PLATE	2mm Plate (SKU 268713)	1.0mm - 5.5mm (Unadjusted Reveal: 1mm)	1.0mm - 4.5mm (Unadjusted Reveal: 0mm)	1.0mm - 3.5mm (Unadjusted Reveal: -1mm)	1.0mm - 2.5mm (Unadjusted Reveal: -2mm)

MINIM	1 164		
	UIVI	KEV	EAL

		BORE DISTANCE			
		Змм	4мм	5мм	6мм
S	16мм	1.0mm	1.0mm	1.0mm	1.0mm
DOOR THICKNESS	17мм	1.2mm	1.2mm	1.1mm	1.1mm
	18мм	1.4mm	1.3mm	1.2mm	1.2mm
	19мм	1.6mm	1.5mm	1.5mm	1.4mm
	20мм	1.9mm	1.8mm	1.8mm	1.7mm

*Table values are based on doors with square edges. Numbers are reduced for doors with radiused edges.

Hardware **Source**

APPOXIMATE CONVERSION			
CONVERSION			
3mm	1/8"		
4mm	5/32"		
5mm	3/16"		
5.5mm	7/32"		
6mm	1/4"		
7mm	9/32"		
8mm	5/16"		
9mm	11/32"		
9.5mm	3/8"		
10mm	13/32"		
11mm	7/16"		
12mm	15/32"		
13mm	1/2"		
13.5mm	17/32"		
14mm	9/16"		
15mm	19/32"		
16mm	5/8"		
17mm	11/16"		
18mm	23/32"		
19mm	3/4"		
20mm	25/32"		
20.5mm	7/8"		
21mm	27/32"		
22mm	7/8"		
23mm	29/32"		
24mm	15/16"		
25.4mm	1"		
26mm	1–1/32"		
27mm	1–1/16"		
28mm	1–3/32"		
29mm	1–1/18"		
30mm	1–3/16"		
31mm	1–7/32"		
32mm	1–1/4"		
33mm	1–5/16"		
34mm	1–11/32"		
35mm	1–3/8"		
36mm	1-13/32"		