
# Blum 170 Degree Half Cranked Hinge for Inset Doors REVEAL TABLES

### WHAT IS A REVEAL?

When a door swings, it needs a certain amount of clearance at both ends of the door so that anything close (ie. another door or a side panel) does not interfere with the opening door. This clearance gap is called the reveal. The table below shows the minimum amount of reveal needed for this hinge.

# FOR INSET DOORS

The minimum reveal is very important for inset doors. For inset doors, the reveal is the gap between the edge of the door and the side panel or the edge of the face frame.



## HOW TO USE THESE CHARTS

The first table below shows the reveal between the door and cabinet side wall based on bore distance and mounting plate height. The bore distance is the distance from the edge of the door to the edge of the cup that is drilled in the back of the door. See "B" on the chart to the right for further clarification. When doing replacements, measure and match your existing reveal distance and bore distance to verify if this hinge and plate will work for you.

The second table below shows the minimum amount of reveal required for this hinge depending on bore distance and door thickness. For new installations, start by determining what reveal distance is desired using the first chart. This will tell you the bore distance that's required. Use

BORE HOLE PATTERN
(BACKSIDE OF DOOR)

9.5mm

9.5mm

BOGE OF DOOR)

**B** = Bore Distance **C** = Cup Centerpoin

the second chart to verify that your door thickness will accommodate the desired reveal.

Example: If you want a 0mm reveal, you would use the first chart below to verify how large of a bore distance is required. In this scenario, both a 6mm & 7mm bore distance would work, as the reveal for this hinge is adjustable by +- 2mm. You would then use the second table to determine how thick of a door will allow this reveal. Using your previously acquired bore distance (6 or 7mm), you can now determine that any door thickness ranging from 16mm to 24mm will work, as all options at these bore distances have no minimum reveal.

#### **INSET DOOR REVEAL**

		BORE DISTANCE				
		3мм	4мм	5мм	6мм	7мм
PLATE	<b>9mm Plate</b> (SKU 652302)	4.5mm	3.5mm	2.5mm	1.5mm	0.5mm

#### MINIMUM REVEAL

		BORE DISTANCE				
		3мм	4мм	5мм	6мм	7мм
THICKNESS	16мм	0mm	0mm	0mm	0mm	0mm
	18мм	0mm	0mm	0mm	0mm	0mm
월	19мм	0mm	0mm	0mm	0mm	0mm
DOOR.	22мм	0.2mm	0mm	0mm	0mm	0mm
	24мм	2.2mm	1.4mm	0.9mm	0mm	0mm

<sup>\*</sup>Table values are based on doors where the edges are rounded with a 1mm radius. Numbers are reduced for doors with larger radiused corners.

HardwareSource

APPOXIMATE CONVERSION CHART				
3mm	1/8"			
4mm	5/32"			
5mm	3/16"			
5.5mm	7/32"			
6mm	1/4"			
7mm	9/32"			
8mm	5/16"			
9mm	11/32"			
9.5mm	3/8"			
10mm	13/32"			
11mm	7/16"			
12mm	15/32"			
13mm	1/2"			
13.5mm	17/32"			
14mm	9/16"			
15mm	19/32"			
16mm	5/8"			
17mm	11/16"			
18mm	23/32"			
19mm	3/4"			
20mm	25/32"			
20.5mm	7/8"			
21mm	27/32"			
22mm	7/8"			
23mm	29/32"			
24mm	15/16"			
25.4mm	1"			
26mm	1–1/32"			
27mm	1–1/16"			
28mm	1–3/32"			
29mm	1–1/18"			
30mm	1–3/16"			
31mm	1–7/32"			
32mm	1–1/4"			
33mm	1–5/16"			
34mm	1–11/32"			
35mm	1–3/8"			
36mm	1-13/32"			