HARDWARESOURCE HINGE SKU 652362

Blum Thick Door Hinge For Frameless Inset Cabinets **REVEAL TABLES**

	WHAT IS A REVEAL?	When a door swings, it needs a certain amount of clearance at both ends of the door so that anything close (ie. another door or a side panel) does not interfere with the opening door. This clearance gap is called the reveal. The table below shows the minimum amount of reveal	CONVI	KIMATE ERSION ART
		needed for this hinge.	3mm	1/8"
			4mm	5/32"
		The minimum reveal is very important for inset doors. For inset doors,	5mm	3/16"
	FOR INSET	the reveal is the gap between the edge of the door and the side panel or the edge of the face frame.	5.5mm	7/32"
	DOORS		6mm	1/4"
		(aleal	7mm	7mm 9/32"
		The first table below shows the reveal between the door and cabinet side	8mm	5/16"
		wall based on bore distance and mounting plate height. The bore distance	9mm	11/32"
		is the distance from the edge of the door to the edge of the cup that is drilled in the back of the door. See "B" on the chart to the right for further	9.5mm	3/8"
		clarification. When doing replacements, measure and match your existing	10mm	13/32"
			11mm	7/16"
			12mm	15/32"
	HOW TO	The second table below shows the minimum amount of reveal required for this hinge depending on bore distance and door thickness. For new	13mm	1/2"
	USE THESE CHARTS	installations, start by determining what reveal distance is desired using	13.5mm	17/32"
	CHARIS	the first chart. This will tell you the bore distance that's required. Use the second chart to verify that your door thickness will accommodate the B = Bore Distance C = Cup Centerpoint	14mm	9/16"
		desired reveal.	15mm	19/32"
		Example: If you want a 2mm reveal, you would use the first chart verify how large of a bore distance	16mm	5/8"
		is required. In this case it would be 5mm. You would then use the second table to determine how	17mm	11/16"
		thick of a door will allow this reveal. Using your previously acquired bore distance (5mm), you can now determine that a door between 19mm and 28mm thick will allow a 2mm reveal. If you need to	18mm	23/32"
		now determine that a door between 19mm and 20mm thick will allow a 2mm reveal. If you need to	10	2/1"

	MINIMUM REVEAL					
		BORE DISTANCE				
		Змм	4мм	5мм	6мм	7мм
LATE	Omm Plate (SKU 652296)	4mm	3mm	2mm	1mm	N/A

use a thicker door, you would need to increase your reveal by decreasing your bore distance.

	MINIMUM REVEAL					
		BORE DISTANCE				
		Змм	4мм	5мм	6мм	7мм
	19мм	0.4mm	0.4mm	0.4mm	0.4mm	0.4mm
ESS	22мм	0.8mm	0.7mm	0.7mm	0.7mm	0.7mm
Z	24мм	1.0mm	1.0mm	1.0mm	1.0mm	0.9mm
DOOR THICKNESS	26мм	1.5mm	1.4mm	1.4mm	1.4mm	1.4mm
NOR NOR	28мм	1.9mm	1.8mm	1.8mm	1.8mm	1.7mm
8	29мм	2.8mm	2.5mm	2.3mm	2.2mm	2.1mm
	30мм	3.6mm	3.1mm	2.7mm	2.5mm	2.4mm

*Table values are based on doors where the edges are rounded with a 1mm radius. Numbers are reduced for doors with larger radiused corners. Hardware**Source**

CHART				
3mm	1/8"			
4mm	5/32"			
5mm	3/16"			
5.5mm	7/32"			
6mm	1/4"			
7mm	9/32"			
8mm	5/16"			
9mm	11/32"			
9.5mm	3/8"			
10mm	13/32"			
11mm	7/16"			
12mm	15/32"			
13mm	1/2"			
13.5mm	17/32"			
14mm	9/16"			
15mm	19/32"			
16mm	5/8"			
17mm	11/16"			
18mm	23/32"			
19mm	3/4"			
20mm	25/32"			
20.5mm	7/8"			
21mm	27/32"			
22mm	7/8"			
23mm	29/32"			
24mm	15/16"			
25.4mm	1"			
26mm	1–1/32"			
27mm	1–1/16"			
28mm	1–3/32"			
29mm	1–1/18"			
30mm	1–3/16"			
31mm	1–7/32"			
32mm	1–1/4"			
33mm	1–5/16"			
34mm	1–11/32"			
35mm	1–3/8"			
36mm	1-13/32"			