
Blum 110 Degree Full Cranked Hinge for Frameless Inset Cabinets **REVEAL TABLES**

WHAT IS A REVEAL?

When a door swings, it needs a certain amount of clearance at both ends of the door so that anything close (ie. another door or a side panel) does not interfere with the opening door. This clearance gap is called the reveal. The table below shows the minimum amount of reveal needed for this hinge.

FOR INSET DOORS


The minimum reveal is very important for inset doors. For inset doors, the reveal is the gap between the edge of the door and the side panel or the edge of the face frame.



HOW TO **USE THESE CHARTS**

The first table below shows the reveal between the door and cabinet side wall based on bore distance and mounting plate height. The bore distance is the distance from the edge of the door to the edge of the cup that is drilled in the back of the door. See "B" on the chart to the right for further clarification. When doing replacements, measure and match your existing reveal distance and bore distance to verify if this hinge and plate will work for you.

The second table below shows the minimum amount of reveal required for this hinge depending on bore distance and door thickness. For new installations, start by determining what reveal distance is desired using the first chart. This will tell you the bore distance that's required. Use the second chart to verify that your door thickness will accommodate the desired reveal.



Example: If you want a 1mm reveal, you would use the first chart verify how large of a bore distance is required. In this case it would be 6mm. You would then use the second table to determine how thick of a door will allow this reveal. Using your previously acquired bore distance (6mm), you can now determine that a 16mm and 19mm thick door will allow a 1mm reveal. If

you were to use a 22mm thick door, this would not work as it requires at least a 1.6mm reveal.

INSET DOOR REVEAL

		BORE DISTANCE				
		3мм	4мм	5мм	6мм	7мм
PLATE	Omm Plate (SKU 652296)	4mm	3mm	2mm	1mm	N/A

MINIMUM REVEAL

		BORE DISTANCE				
		3мм	4мм	5мм	6мм	7мм
DOOR THICKNESS	16мм	0.5mm	0.5mm	0.5mm	0.5mm	0.5mm
	19мм	1mm	1mm	0.9mm	0.9mm	0.9mm
	22мм	1.8mm	1.7mm	1.7mm	1.6mm	1.6mm
	24мм	2.7mm	2.5mm	2.4mm	2.3mm	2.2mm
	26мм	4.3mm	3.8mm	3.4mm	3.2mm	3.0mm

∗Table values are based on doors where the edges are rounded with a 1mm radius. Numbers are reduced for doors with larger radiused corners.

HardwareSource

APPOXIMATE CONVERSION CHART					
3mm	1/8"				
4mm	5/32"				
5mm	3/16"				
5.5mm	7/32"				
6mm	1/4"				
7mm	9/32"				
8mm	5/16"				
9mm	11/32"				
9.5mm	3/8"				
10mm	13/32"				
11mm	7/16"				
12mm	15/32"				
13mm	1/2"				
13.5mm	17/32"				
14mm	9/16"				
15mm	19/32"				
16mm	5/8"				
17mm	11/16"				
18mm	23/32"				
19mm	3/4"				
20mm	25/32"				
20.5mm	7/8"				
21mm	27/32"				
22mm	7/8"				
23mm	29/32"				
24mm	15/16"				
25.4mm	1"				
26mm	1–1/32"				
27mm	1–1/16"				
28mm	1–3/32"				
29mm	1–1/18"				
30mm	1–3/16"				
31mm	1–7/32"				
32mm	1–1/4"				
33mm	1–5/16"				
34mm	1–11/32"				
35mm	1–3/8"				
36mm	1-13/32"				