



ACCENT RELEASE LIQUID

CLEAR BOND BREAKER FOR CONCRETE TEXTURING MATS

Specco Accent Release Liquid is a specially formulated colorless bond breaker designed to prevent freshly placed concrete from adhering to texturing mats. **Accent Release Liquid** forms a lubricating barrier that prevents sticking, concrete build up, and friction between the texturing mats and the freshly placed concrete. Primary uses are on plain or integrally pigmented concrete and in combination with Dry Shake Colored Hardeners.

BENEFITS:

- Excellent release characteristics
- Allows monotone stamping (clear) option
- Allows release in areas where powders cannot be used
- Easy to use with less mess and clean up
-

COMPOSITION: Proprietary blend of slow drying hydrocarbon-based solvents and surface acting chemicals

LEED CREDIT CONSIDERATIONS: Materials and Resources: **MR Credits 5.2:** Regional materials- Greater than 20% extracted, processed and manufactured regionally at production location: Kankakee, Illinois 60901. 90% Content- Harvested < 500 miles

PHYSICAL PROPERTIES at 70° F (21°C):	APPROXIMATE VALUES:
Weight per Gallon:	6.55 +/- 0.10 lb./ gallon
Color& Odor	Light clear liquid with bubblegum fragrance
Viscosity-Brookfield:	5 cps
Flash Point:	150° F (65.5°C)
V.O.C. Content:	445 g/L (3.71 lb./ gallon) per EPA Method 24*

***VOC COMPLIANCE:** **Accent Release Liquid** contains less than 450 g/L (3.75 lb. /gal.) volatile organic compounds. Meets Architectural Coatings Section 183(e) Final Rule Limit for release agents for most states, excluding California & New Jersey.

DIRECTIONS FOR USE: Place, vibrate and float the concrete surface according to standard **ACI** recommendations. Cover or protect adjacent surfaces. Following the initial floating, when excess moisture is no longer evident, apply **Accent Release Liquid** liberally to the texture mats and to the concrete using a garden type sprayer. To avoid evaporation of the material, apply only in the area where the next few mats are to be placed. One gallon of **Accent Release Liquid** will be sufficient for approximately 150 square feet of concrete surface. Immediately begin the texturing application. Do not trowel or mix into the plastic concrete surface. To make corrections on the plastic concrete surface, use the texturing tool to press out unwanted impressions. Upon completion of the stamping process, clean texturing mats using plain water. After 24 hour wait time, seal the textured concrete surface with Specco **Stampsheen 350** for a high gloss finish.

CLEAN UP: Due to its low solids formulation, **Accent Release Liquid** can typically be left inside the sprayer vessel and will not clog sprayer tip for future applications if it is not purged out after job completion. However, if the sprayer needs to be cleaned out completely, then Specco recommends the use of **Regular Grade Mineral Spirits** to purge remaining residue inside sprayer chamber.

CAUTIONS: Use **Accent Release Liquid** only on the immediate area to be imprinted. Do not trowel or mix into plastic concrete.





GHS HAZARD RATINGS: WARNING:



IRRITANT:
RESPIRATORY TRACT IRRITATION



HEALTH HAZARD:
REPRODUCTIVE TOXICITY

FIRST AID: REFER TO PRODUCT S.D.S. (SAFETY DATA SHEET) FOR COMPLETE HEALTH AND SAFETY INFORMATION BEFORE USING THIS PRODUCT. FOR MEDICAL EMERGENCIES ONLY – CALL INFOTRAC AT 800-535-5053.

WARNINGS & SAFETY INFORMATION: CONTAINS COMBUSTIBLE LIQUID AND VAPORS! USE ONLY IN WELL-VENTILATED AREAS. Store and apply away from heat, sparks, open flames, water heaters, or any related sources of ignition. Empty containers may contain explosive vapors that are heavier than air. Keep containers closed. Do not cut or weld on or near empty containers. Under all circumstances, avoid the introduction of compressed air into the container. Make sure that the product application is static free. Avoid breathing vapors. Wear protective clothing and safety glasses during application. Use with adequate ventilation. Use with OSHA/NIOSH approved eye protection and air (vapor) respirator. This product may cause damage to the liver or kidneys through prolonged or repeated exposure to the skin. Avoid ingestion, skin and eye contact and inhalation of the spray mist. Keep away from food and drink. Wash hands thoroughly after use and before eating. Do not take internally. **FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.**

H.M.I.S. CODES (Hazardous Materials Identification System): HEALTH = 2, FLAMMABILITY = 2, REACTIVITY = 1, PERS. PROT = G

SHIPPING NAME: Mixture: contains Aliphatic Hydrocarbon, CAS # 64742-47-8

SHIPPING CLASS: NA 1993, Petroleum Naphtha, Combustible Liquid N.O.S., 8, III / Item #155250 Sub 2 Freight Class 65 Concrete Release Agent **Note: Not regulated by D.O.T. and no placards required if shipping container is less than 119 gallons capacity. For Combustible Liquid Exemption, refer to CFR 49,173.150 paragraph H.**

PACKAGING: 5 & 55 gallon containers

STORAGE/SHELF LIFE: 40° to 90° F / 3 years- properly stored

WARRANTY: Specco Industries Inc (Specco) solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Specco, no other representations or statements made by Specco or its representatives, in writing or orally, shall alter this warranty. **SPECCO MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME.** If any Specco product fails to conform with this warranty, Specco will replace the product at no cost to Buyer. **Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages.** Specco does not authorize anyone on its behalf to make any written or oral statements which in any way alter Specco's installation information or instructions in its product literature or on its packaging labels. **Specco explicitly excludes any written or oral statements or implied warranty on the performance of an applied/installed product manufactured or sold by or through Specco.** Specco has no control over Specco application standards adherence, site conditions, atmospheric variations, installer/applicator skill level or the determination of the suitability of any Specco products for a specific intended purpose. **Buyer shall be solely responsible for determining the suitability of Specco's products for the Buyer's intended purposes.** Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind.

Revised 08-28-19



601 NORTH 5TH AVE • KANKAKEE, IL • 60901
630-257-5060 **SPECCO.com**

