Safety Data Sheet

Accent Release Powder

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200



SECTION 1. Identification

1.1 Product Identifier:

Product Name: Accent Release Powder **Product Code:** Formulations JB-1104P AR-01-

AR-19

1.2 Uses of the product :

Stamped Concrete Colored Release Powder

1.3 Details of the product manufacturer:

Supplied By: Specco Industries Inc.

601 N. 5th Ave.

Kankakee, Illinois 60901

(630)-257-5060

E-Mail: Info@specco.com

www.specco.com

1.4 Emergency Telephone Number:

24 Hour Emergency:

INFOTRAC: 1-800-535-5053

Outside U.S. and Canada Infotrac: 352-323-3500

Note: INFOTRAC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals

SECTION 2. Hazard(s) Identification

2.1 EMERGENCY OVERVIEW** OSHA Hazards: Harmful if swallowed. May cause slight eye and skin irritation. Harmful if inhaled. Causes damage to lungs though prolonged or repeated exposure by inhalation.

2.2 Classification of the substance or mixture: Target Organs: Lungs GHS-US Classification

STOT SE 3 H335 STOT RE 1 H373

For the full text of H-phrases: See Section 16

2.3 Label elements:





Symbol(s) of Product GHS-US labeling:

Hazard pictograms (GHS-US):

Signal Word: Warning

2.3 Label Elements

GHS-US HAZARD STATEMENTS:

Acute Toxicity Oral-category 4 H302 Harmful if swallowed
Eye Irritation, category 2 H319 Causes serious eye irritation
Lung Irritation, category 2 H335 May cause respiratory irritation

Repeated exposure- category 2 H373 May cause damage to the lungs and / or Respiratory system through prolonged or

repeated inhalation

| P201 | Obtain special instructions before use. |
|--------------------|--|
| P202 | Do not handle until all safety precautions have been read and understood. |
| P260 | Do not breathe dust |
| P261 | Avoid breathing dust/fume/gas/mist/vapors/spray. |
| P264 | Wash hands and forearms thoroughly after handling. |
| P270 | Do not eat, drink or smoke when using this product |
| P272 | Contaminated work clothing should not be allowed out of workplace |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P302 + P352 | IF ON SKIN, Wash with plenty of water. |
| P304 + P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. |
| | Remove contact lenses if present and easy to do. Continue rinsing. |
| P308 + P313 | IF exposed or concerned: Get medical advice/ attention. |
| P312 | Call a POISON CENTER/doctor/physician if you feel unwell. |
| P321 | Specific treatment (see first aid section on this label) . |
| P332 + P313 | If skin irritation occurs: Get medical advice/attention. |
| P337 + P313 | If eye irritation occurs: Get medical advice/attention. |
| P362 + P364 | Take off contaminated clothing and wash it before reuse. |
| P403 + P233 | Store in a well-ventilated place. Keep containers tightly closed |
| P501 | Dispose of contents/container in accordance with |
| | local / regional / national / international regulations. |

2.4 Other hazards:

Hazardous decomposition products: Silica will dissolve in hydrofluoric acid and produce a corrosive gas-silicon tetrafluoride.

SECTION 3. Composition on Ingredients

3.1 Substances:

| Chemical name | CAS-No. | <u>Wt. %</u> | GHS-US Symbols | GHS-US Statements | |
|--------------------------|------------|--------------|----------------|--------------------------|--|
| Calcium Carbonate | 471-34-1 | N.A | GHS07-GHS08 | H315, 319 | |
| Magnesium Carbonate | 12042-78-3 | N.A | GHS07-GHS08 | H315, 319 | |
| Stearic Acid | 57-11-4 | N.A. | GHS07-GHS08 | H315, 319 | |
| Iron (III) Oxides | 1317-60-8 | N.A. | GHS07-GHS08 | H315, 319 | |
| Proprietary- Non Hazard. | N.A. | N.A. | | | |

Note: The full text for GHS Statements shown above (if any) is given in the "Other Information" Sect. (16)

STOT SE = Specific target organ toxicity for a single exposure STOT RE = Specific target organ toxicity for a repeated exposure

SECTION 4. First-Aid Measures

4.1 Description of first aid measures:



FIRST AID- EYE CONTACT: Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly. Remove contact lenses if worn.



FIRST AID- SKIN CONTACT: Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately and clean shoes before reuse.



FIRST AID- INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep

victim warm. Get immediate medical attention.



FIRST AID- INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

4.2 Principle symptoms and health effects both acute and delayed:



EYE CONTACT: Redness, irritation or pain



SKIN CONTACT: Prolonged contact with large amounts of this product may cause mechanical

Irritation. Dust may cause irritation in skin folds or by contact in combination with

tight clothing.



INHALATION: May cause respiratory irritation, sneezing, coughing, burning sensation in the

throat, or constriction in the larynx, or difficulty breathing.



INGESTION: Abdominal pain

CHRONIC SYMPTOMS: Shortness of breath, wheezing, cough and sputum production. May cause cancer, silicosis, lung disease, auto immune disease, tuberculosis, and nephrotoxicity.

4.3 Indication of any immediate medical attention and special treatment needed:

No specific actions are required.

SECTION 5. Fire-Fighting Measures

5.1 Extinguishing Media:

Suitable Extinguishing Media: Use the extinguishing media appropriate for the surrounding fire.

Unsuitable Extinguishing Media: None Known

5.2 Special hazards arising from the substance or mixture:

Fire Hazard: None, this product is not flammable **Explosion Hazard:** None, this product is not explosive

Reactivity: No hazardous combustion products or hazard reactions are known.

5.3 Advice for Firefighters

No specific firefighting instructions are required. Use normal individual personal protective equipment and fight fire from a reasonable distance using normal precautions.

SECTION 6. Accidental Release Measures

6.1 Personal precautions, protective equipment, and emergency procedures

General: Do not breath dust. Avoid generating airborne dust. Collect the material using a method that does not produce dust. (High Efficiency Particulate Air (HEPA) vacuum or thoroughly wetting down the material). Dispose of according to federal, state, and local regulations.

Protective Equipment: Wear protective clothing as appropriate for the work environment, including gloves, and eye/face protection. Use respiratory protection as recommended in Section 8-Exposure controls/personal protection.

Emergency Procedure: Collect as any inert solid

6.2 Environmental precautions:

No special requirements

6.3 Methods and material for containment and cleaning up:

Avoid dry sweeping or otherwise generating dust during clean-up of spills. Use water spraying or vacuum cleaning systems to prevent airborne dust generation. Recover product by vacuuming or shoveling and place the material in a covered container appropriate for disposal.

6.4 Reference to other Sections:

Refer to Sections 8 and 13 for additional information

SECTION 7. Handling and Storage

7.1 Precautions for safe handling:

Work Practices: Avoid airborne dust generation. Provide appropriate exhaust ventilation at places where airborne dust is generated. Do not rely on vision to determine whether respirable silica is present in the air since it may be present without a visible cloud. In case of insufficient ventilation, wear respiratory protective equipment as recommended in Section 8. Handle packaged products carefully to prevent bursting. If you require advice on safe handling techniques, please contact your supplier or check the Good Practices Guide referenced in Section 16.

Hygiene Practices: Do not eat, drink, or smoke in work areas. Wash hands after use. Remove contaminated clothing and protective equipment before entering eating areas.



7.2 Conditions for safe storage, including any incompatibilities:

Technical measures: Minimize airborne dust generation and prevent wind dispersal during loading and unloading.

7.3 Specific end use(s):

Intended Use(s): Antiquing powder for stamped concrete surfaces

Prohibited use(s): None listed

Precautions: Store containers/ a bags in a cool dry place away from moisture. Keep containers closed and store packaged products so as to prevent accidental busting. Keep containers/bags closed when not in use.

SECTION 8. Exposure Controls/Personal Protection

8.1 Control Parameters:

Ingredients with Occupational Exposure Limits

| Chemical Name | ACGIH-TLV-TWA | ACGIH-TLV STEL | OSHA PEL-TWA | OSHA PEL-CEILING |
|-----------------------------|---------------|-----------------------|---------------------|-------------------------|
| Calcium Carbonate | 10 mg/m3 | N.E. | 10mg/m3 | N.E. |
| Magnesium Carbonate | 10 mg/m3 | N.E. | 10mg/m3 | N.E. |
| Stearic Acid | 10 mg/m3 | N.E. | 10mg/m3 | N.E. |
| Iron (III) Oxides | 0.1 mg/m3 | N.E. | 0.1mg/m3 | N.E. |
| Proprietary (Non-Hazardous) | NA | N.E. | NA | N.E. |

CAUTION:

Crystalline silica exists in several forms, the most common on which is quartz. If crystalline silica (quartz) is heated to more than 870 deg C (1598 deg F), it can change to a form of crystalline silica known as trydimite, and If crystalline silica (quartz) is heated to more than 1470 deg C (2,678 def F), it can change to a form of crystalline silica known as cristoblite. Crystalline silica as trydimite or crisitobalite are more fibrogenic than crystalline silica known as

quartz. The OSHA/MSHA PEL for crystalline silica as tryimite and cristobalite is one half the PEL for crystalline silica (quartz.). The ACGIH TLV for crystalline silica as cristobalite is equal to the TLV for crystalline silica as quartz.

8.2 Exposure controls:

8.2.1 Engineering controls:

Minimize the generation of airborne dust. Use process controls, local exhaust ventilation, or other engineering controls to maintain airborne levels below the limits shown in Section 8.1 above. See also ACGIH Industrial Ventilation-Recommended Practice (latest edition).

8.2.2 Personal protective equipment (PPE):



RESPIRATORY PROTECTION: Avoid breathing dust produced during the use and handling of this product. A NIOSH/MSHA approved air purifying respirator with a HEPA cartridge is required under circumstances where airborne concentrations are less than 0.1 mg/ m3 (10 X PEL). Typically, a half-mask air purifying respirator with a P-100 HEPA filter approved by NIOSH is sufficient for use with this product. For application concentrations greater than this particulate threshold, full face piece air purifying respirators or any air powered-purifying respirators can be utilized for proper protection levels. If the workplace airborne crystalline silica concentration is unknown for a given task, conduct air monitoring to determine the appropriate level of respiratory protection needed. Consult with a certified industrial hygienist, your insurance risk manager, or the OSHA/MSHA Consultive Services Group for more information. Ensure appropriate respirators are worn during job tasks, including clean-up or whenever airborne dust is present, in order to manage employee exposures below occupational health limits.



SKIN PROTECTION: Wear impervious, impermeable gloves to prevent contact with the skin. Wear protective gear as needed such as apron, long sleeved shirts in situations where abrasion from sand may occur. Wash hands with soap and water after use.



EYE PROTECTION: Goggles are recommended where airborne dust is produced.



OTHER PROTECTIVE EQUIPMENT: None



HYGENIC PRACTICES: Do not eat or drink in areas where the material is used. Avoid breathing dust. Remove contaminated clothing and wash before re-use. Wash thoroughly after handling. Wash hands before eating.

SECTION 9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties:

Appearance: Earth Tone Powders Physical State: Powder 18 different shades Odor : None

Density, g/cm3: Approx. 1.20 **pH:** 9.0 (diluted).

Freeze Point, °F: N.A. Viscosity: N.A. Solubility in Water: N.A. Explosive Limits,vol%: N.A.

Boiling Range, F: N.A. Flash Point, °F: N.A. Evaporation Rate: N.A. Auto Ignition Temp, °F: N.A. Vapor Density: N.A. Vapor Pressure: N.A.

9.2 Note: See "Other Information" Section (16) for abbreviation legend

SECTION 10. Stability and Reactivity

10.1 Reactivity:

Inert, not reactive

10.2 Chemical stability:

Stable under normal temperature and pressure

10.3 Possibility of hazardous reactions:

Hazardous reactions or polymerization will not occur.

10.4 Conditions to avoid:

None Known

10.5 Incompatible materials:

Strong oxidizing agents such as fluorine, chlorine trifluoride, hydrogen fluoride, and oxygen difluoride.

10.6 Hazardous decomposition products:

Silica will dissolve in hydrofluoric acid and produce a corrosive gas- silicon tetrafluoride.

SECTION 11. Toxilogical Information

Information on Toxilogical Effects

Likely Routes of Exposure: Inhalation, Skin Contact, Eye Contact, Ingestion

Numerical measures of toxicity: NA

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-Term

exposure:NA

SECTION 12. Ecological Information

12.1 Toxicity

Not relevant

12.2 Persistence and degradability

Not biodegradable.

12.3 Bioaccumulative potential

Not known to bioaccummulate.

12.4 Mobility in Soil

Negligible

12.5 Other adverse effects

No other specific adverse effects known

SECTION 13. Disposal Considerations



13.1 Waste treatment methods

General: The unused product residue may be landfilled and is not expected to be a hazardous waste under RCRA.

Packaging: Material should be placed in covered containers to minimize generation of airborne dust. Place spilled material into a container. Scrape wet material and place into a container. Allow material to dry or solidify before disposal.

RCRA: None

NOTE: Always dispose of any waste in accordance with all local, state, and federal regulations.

SECTION 14. Transport Information

14.1 UN Number:

Not relevant- Not a dangerous good

14.2 UN Proper Shipping Name:

Item#149980, Sub 7, Freight Class 60 Iron oxide powder mixture in pails

14.3 Transport hazards class:

None

14.4 Packing Group:

Not applicable'

14.5 Environmental hazards:

Not relevant

14.6 Special precautions for user:

No special precautions

SECTION 15. Regulatory Information

15.1 U.S. Federal Regulations:

TSCA No:

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances. None

SARA SECTIONS:

302: None known. **311/312** Delayed Health Hazard **313** Hazard Categories: None

RCRA:

None

CERCLA:

None.

EMERGENCY PLANNNING AND COMMUNITY RIGHT TO KNOW ACT: None

CLEAN AIR ACT:

This product does not contain any Class I or Class II ozone depleting substances.

FDA:

None

NTP:

None

OSHA:

None.

15.2 U.S, State Regulations:

CALIFORNIA PROPOSITION 65:

This product contains or may contain chemicals known to the state of California to cause cancer and birth defects or other reproductive harm:

| Chemical name: | CAS# | Concentration | State Code |
|------------------|-----------|---------------|---------------|
| Black Iron Oxide | 1317-61-9 | < 10% | PA3, NJ4 |
| Red Iron Oxide | 1309-37-1 | < 10% | PA3, NJ4, CN1 |
| Lead | 7439-92-1 | <100ppm | CA, MA |
| Cadmium | 7440-43-9 | <5 ppm | CA, MA |
| Arsenic | 7440-38-2 | <50ppm | CA, MA |
| Copper | 7440-50-8 | <800ppm | CA, MA |
| Manganese | 7439-96-5 | <2000ppm | CA, MA |
| Mercury | 7429-97-6 | <1ppm | CA |
| Nickel | 7440-02-0 | <400 ppm | CA, MA |

^{*}Note- This information is based on random sample analysis. Actual content may vary from batch to batch

CALIFORNIA INHALATION REFERENCE EXPOSURE LIMIT (REL):

None.

15.3 International regulations:

CANADIAN WHMIS:

Not restricted/ Non-hazardous

All components of this product are on the Domestic Substances List (DSL), and ae acceptable for use under the provisions of CEPA.

WHMIS Class: NA

EUROPEAN UNION:

All components of this product are on the European Inventory of Exisitng Commercial Chemical Substances.

IARC:

NA

15.4 Other Regulations

National, state, provincial or local emergency planning, community right to know or other laws, regulations or ordinances may be applicable-consult applicable national, state, provincial or local laws.

SECTION 16. Other Information

Revision Date: 12-11-19 Supersedes Date: 11-26-19

S.D.S. produced by: Specco Regulatory Department in accordance with the requirements outlined in the Federal Register, Volume 77, NO.58, March 2012 page 17574. In this final rule, OSHA modified its Hazard Communication Standard (HCS) to conform to the United Nation's Globally Harmonized System of Classification and Labeling of Chemicals (GHS). The modifications to the standard included but were not limited to revised criteria for classification of chemical hazards and a new specified format for Safety Data Sheets.

Standardized American System for the identification of hazards presented by this product in view of emergency procedures (NFPA 704) -H.M.I.S. Ratings:



* Refer to Section 2 and Section 11 of this SDS

Text for GHS Hazard Statements shown in section 3 describing each ingredient:

H315 Causes skin irritation

H319 Causes serious eye irritation

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS07



GHS08



Legend: * Refer to 49 CFR for possible exceptions and exemptions. Abbreviations: TLV= Threshold Limit Value. TWA= Time Weighted Average. STEL= Short Term Exposure Limit. N.A. = Not Applicable. N.D. = Not Determined, N.E. =Not Established. IATA= International Air Transport Association. IMDG= International Maritime Dangerous Goods.

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge, For these reasons we do not assume responsibility and expressly disclaim any liability from loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.