



# EZCURB™ SYSTEM

## SATIN FINISH SEALER

**EZCURB™ Satin Finish Sealer** is a high solid, satin finish, clear solvent based acrylic copolymer, used to cure and seal freshly placed concrete curbs. **Satin Finish Sealer** forms an impervious film which resists the alkali present in freshly placed concrete curbs and retains moisture ensuring proper strength development. It penetrates and provides a protective seal on the curb's surface that is resistant to mild acid, alkali, and anti-fungal. **Satin Finish Sealer** increases stain resistance and promotes easier cleaning and extended wear.

### BENEFITS:

- **Hardens new concrete curbs by providing proper cure**
- **Protects and enhances curb color with a tough durable film**
- **Excellent stain resistance and anti-fungal properties**
- **UV resistant formula will not yellow from sun degradation**

**DIRECTIONS:** Apply **Satin Finish Sealer** by short nap (solvent resistant) roller or lamb's wool applicator. No mixing required. For optimum curing performance, apply after final finishing when there is no visible surface water. For best appearance and performance, apply uniformly at a recommended coverage rate of 250 Linear Feet per gallon. If a second coat is desired, apply at a rate of 350 linear feet per gallon.

**CAUTIONS:** Do not apply when temperature exceeds 90° F, and if rain is expected within 24 hours. Avoid direct sunlight when possible.

### GHS HAZARD RATINGS: DANGER:



**IRRITANT**  
**RESPIRATORY, EYES,  
AND SKIN**



**HEALTH HAZARD:**  
**SUSPECTED  
CARCINOGEN**



**HEALTH HAZARD:**  
**FLAMMABLE  
LIQUID**

**FIRST AID: REFER TO PRODUCT S.D.S. (SAFETY DATA SHEET) FOR COMPLETE HEALTH AND SAFETY INFORMATION BEFORE USING THIS PRODUCT. FOR MEDICAL EMERGENCIES ONLY – CALL INFOTRAC AT 800-535-5053.**

**WARNINGS: CONTAINS FLAMMABLE LIQUID AND VAPORS! USE ONLY FOR EXTERIOR APPLICATIONS.** Keep containers closed when not in use. Wear protective clothing and safety glasses during application, as well as an OSHA/NIOSH approved vapor respirator. Avoid skin and eye contact and inhalation of the spray mist. Keep away from food and drink. Do not take internally.

**FOR PROFESSIONAL USE ONLY • KEEP OUT OF REACH OF CHILDREN.**

**PACKAGING:** 5 gallon containers    **STORAGE/SHELF LIFE:** 40° to 90° F / 3 years- properly stored

**WARRANTY:** Specco Industries Inc (Specco) solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Specco, no other representations or statements made by Specco or its representatives, in writing or orally, shall alter this warranty. **SPECCO MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME.** If any Specco product fails to conform with this warranty, Specco will replace the product at no cost to Buyer. **Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages.** Specco does not authorize anyone on its behalf to make any written or oral statements which in any way alter Specco's installation information or instructions in its product literature or on its packaging labels. **Specco explicitly excludes any written or oral statements or implied warranty on the performance of an applied/installed product manufactured or sold by or through Specco.** Specco has no control over Specco application standards adherence, site conditions, atmospheric variations, installer/applicator skill level or the determination of the suitability of any Specco products for a specific intended purpose. Buyer shall be solely responsible for determining the suitability of Specco's products for the Buyer's intended purposes.



601 NORTH 5TH AVE • KANKAKEE, IL • 60901  
630-257-5060 **SPECCO.com**



REVISED: 07-11-22JB