

FINISHING CLEANER

CONCENTRATED CLEANING AGENT FOR USE WITH GREEN EZ™STRIP & CLEAN ADHESIVE & COATING REMOVER

Green EZ™ Strip & Clean Finishing Cleaner is an environmentally safe cleaning solution formulated primarily with biodegradable based ingredients. Green EZ™ Strip & Clean Finishing Cleaner is designed for complete removal of adhesive, coatings and mastic residue. Green EZ™ Strip & Clean Finishing Cleaner is an environmentally friendly formula manufactured with very low VOC's and may qualify for project LEED credits.

BENEFITS:

- > Removes dissolved paint, sealer, mastic, and coating residue from floor stripping applications
- Low odor for safe indoor use
- Concentrated formula for cost reduction
- Environmentally friendly LEED generating
- ➢ Green EZ™ Strip & Clean System component

COMPOSITION: Contains biodegradable components and alkaline builders, no phosphates or solvents.

LEED CREDIT CONSIDERATIONS: EQ Credit 4.2: Low emitting materials (VOC < 25 g/L). Materials and Resources: **MR Credit 5.2:** Regional materials- Greater than 20% extracted, processed and manufactured regionally at production location: Kankakee, Ll. 60901. 90% Content- Harvested within 500 miles. **MR Credit 6.2:** Rapidly renewable materials.

| PHYSICAL PROPERTIES at 70° F (21°C): | APPROXIMATE VALUES: |
|--------------------------------------|--|
| Weight per Gallon: | 8.55 +/- 0.10 lb./ gallon |
| Color & Odor: | Clear liquid with very mild odor |
| VOC content: | 20 g/L, or 0.16 lb./ gallon |
| pH: | 8.00 (+/- 0.10) measured at 1 to 3 dilution with water |
| Flashpoint: | None |

COVERAGE / SUGGESTED DILUTION / USE RATIOS: Approx. 175-225 sq. ft./gallon. Actual square footage will depend on dilution rate used as well as method of application

SUGGESTED DILUTION / USE RATIOS: Dilute *Green EZ™ Strip & Clean Finishing Cleaner* 1:3 by volume with clean water for normal coatings, adhesive and mastic residual removal. For tougher, heavily deposited residuals use at full strength.

APPLICATION: Apply the diluted or concentrated *Green EZ™ Strip & Clean Finishing Cleaner* solution generously to the surface to be cleaned by simply by pouring or spraying onto horizontal surface. Spread and agitate lightly with a brush.







Allow the *Green EZ™ Strip & Clean Finishing Cleaner* adequate time to dwell, typically 1 hour, scrub again and remove with wet vacuum. Rinse the surface with water, wet-vacuum and check surface for residue. Additional rinsing may be required.

CLEAN-UP: Clean all equipment with soap and water.

CAUTIONS: For best results, do not apply *Green EZ™ Strip & Clean Finishing Cleaner* when surfaces are below 40°F (4°C) or above 90°F (31°C). Do not mix or dilute *Green EZ™ Strip & Clean Finishing Cleaner* with any other materials. *Green EZ™ Strip & Clean Cleaning Agent* will be slippery until cleaned and removed.

GHS HAZARD RATING: WARNING



FATION



RESPIRATORY TRACT, SKIN, AND EYE IRRITATION

TARGET ORGAN TOXICITY- HARMFUL IF INGESTED

FIRST AID: REFER TO PRODUCT S.D.S. (SAFETY DATA SHEET) FOR COMPLETE HEALTH AND SAFETY INFORMATION BEFORE USING THIS PRODUCT. FOR MEDICAL EMERGENCIES ONLY —CALL INFOTRAC AT 800-535-5053.

WARNINGS & SAFETY INFORMATION: GREEN EZ™STRIP & CLEAN FINISHING CLEANER IS RELATIVELY SAFE TO USE. KEEP CONTAINERS CLOSED. AVOID INGESTION, SKIN AND EYE CONTACT AND INHALATION OF THE SPRAY MIST. KEEP AWAY FROM FOOD AND DRINK. WASH HANDS THOROUGHLY AFTER USE AND BEFORE EATING. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.

H.M.I.S. CODES (Hazardous Materials Identification System):

HEALTH = 2, FLAMMABILITY = 0, REACTIVITY = 0, PERSONAL PROTECTION = G (Glasses, Gloves, Respirator)

PACKAGING: 1 quart (6/case), 1 gallon (4 /case) or 5 gallon pails

FREIGHT CLASS: ITEM 33880, Sub 2, Freight Class 55

SHIPPING NAME: Concrete Degreaser Solution-Water Base - Not Regulated

STORAGE: 40° to 90° F. Protect from freezing.

SHELF LIFE: 1 year properly stored





WARRANTY: Specco Industries, Inc. (Specco) solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. No other representations or statements made by Specco representatives, in writing or orally, shall alter this warranty. Specco MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages.

Specco explicitly excludes any written or oral statements or implied warranty on the performance of an applied/installed product manufactured or sold by Specco or through a Specco authorized distributor or reseller. Specco has no control over adherence to Specco's application standards, site conditions, atmospheric variations, installer/applicator skill level or the determination of the suitability of any Specco products for a specific intended purpose. Buyer shall be solely responsible for determining the suitability of Specco's products for the Buyer's intended purposes.

REVISED: 10-19-20W



