TROOPER SPK2

LEVEL 2 SPIKE/STAB













WΔTFR

MADE

011500

LIGHTWEIGHT

LEVEL 2

The Trooper SPK2™ protects against multiple Level 2 medium energy spike threats. The SPK2 has been certified to meet or exceed spike and stab resistant threats as specified under NIJ Standard 0115.00. Extremely lightweight and ultra-thin, the SPK2 is ideal for extended wear and can be easily concealed under the uniform or worn during covert missions.

KEY FEATURES

- Ultra-thin
- Ultra-lightweight
- Level 2 spike/stab coverage



SPECIFICATIONS

- Protection (Spike Level 2): This armor protects against medium energy threats with a strike energy of 33 J (24.3 ftlbf). The over test condition for this level is 50 J (36.9 ft·lbf).
- NIJ Standard 0115.00 CERTIFIED: This product is NIJ 0115.00 compliant "Certified" by NIJ and can be found listed on the NIJ's CPL
- Areal Density: 0.585 psf (2.85 kg/m²)
- Thinness: 0.13" or 3.3mm

- Material: Advanced spike resistant protective fabric, utilizing DuPont™ Kevlar®
- Multi-hit capabilities
- Ultra-lightweight and ultra-thin construction
- Panel Cover: Nylon Ripstop
- Custom sizing available
- Warranty: 5 years on all spike material, 1 year on exterior cover material and workmanship







TACTICAL











CONCEALABLE

BALCS/CIRAS

APC

TORSO

SIDE CUMMERBUND

K-9

STAB/SPIKE PROTECTION		
PROTECTION LEVEL	E1 STRIKE ENERGY	E2 OVERTEST STRIKE ENERGY
2	$33 \pm 0.60 \text{ J}$ 24.3 ± 0.44 ft lbf	50 ± 0.70 J 36.9 ± 0.51 ft lbf

ENGINEERED TO PROTECT

HIGHCOMARMOR.COM

TROOPER SPK3

LEVEL 3 SPIKE/STAB













LEVEL 3

011500

LIGHTWEIGHT

WATER

The Trooper SPK3™ stab and spike resistant soft armor panel protects against Level 3 high energy spike threats. Certified to NIJ Standard 0115.00, the SPK3 is an ultra-thin and lightweight panel, able to protection from multiple stab and spike impacts. Recommended for officers seeking the maximum level of stab protection. The SPK3 slim profile

KEY FEATURES

- Ultra-thin
- Lightweight
- Level 3 spike/stab coverage

makes it ideal for covert missions.



SPECIFICATIONS

- Protection (Spike Level 3): This armor protects against high energy threats with a strike energy of 43 J (31.7 ft- lbf). The over test condition for this level is 65 J (47.9 ft·lbf).
- NIJ Standard 0115.00 CERTIFIED: This product is NIJ 0115.00 compliant "Certified" by NIJ and can be found listed on the NIJ's CPL
- Areal Density: $0.710 \text{ psf} (3.47 \text{ kg/m}^2)$
- Thinness: 0.163" or 4.1mm

- Material: Advanced spike resistant protective fabric, utilizing DuPont™ Kevlar®
- Multi-hit capabilities
- Panel Cover: Nylon Ripstop
- Custom sizing available
- Warranty: 5 years on all spike material, 1 year on exterior cover material and workmanship

PANEL TYPES











APC







CONCEALABLE

TACTICAL

BALCS/CIRAS

TORSO

SIDE CUMMERBUND

STAB/SPIKE PROTECTION		
PROTECTION LEVEL	E1 STRIKE ENERGY	E2 OVERTEST STRIKE ENERGY
3	43 ± 0.60 J 31.7 ± 0.44 ft lbf	65 ± 0.80 J 47.9 ± 0.59 ft lbf

ENGINEERED TO PROTECT

HIGHCOMARMOR.COM