



ASSEMBLY INSTRUCTIONS FOR ACE-TSK-CHAIR

Parts List

A. Back cushion with back support-----	1set
B. Armrest-----	1pair
C. Seat cushion-----	1pc
D. Mechanism-----	1pc
E. Screws (1/4"*3/4") with washer-----	4sets
F. Screws(1/4"*1") with washer -----	6pcs
G. Screws(1/4"*7/4") with washer-----	3sets
H. Cylinder -----	1pc
I . Base -----	1pc
J. Casters-----	5pcs

Assembly Instructions:

Carefully unpack all parts and identify them with the parts list before attempting to assemble:

1. Remove all cardboard and plastic covering from chair parts.
2. Attach both left and right Armrest (B) onto the bottom side of seat cushion (C) by using 6 screws with washers (F).
3. Attach the Mechanism (D) onto the bottom side of seat by using 4 screws (E).
4. Attach the underside of back cushion (A) into the bottom side of aggregation of mechanism and seat cushion and armrest (B/D/C) by using 3sets Screws with washer (G).
5. Push the 5 casters (J) into the holes on the top of the 5 star base (I).
6. Insert the gas cylinder (H) into the center holes on the top of 5 star base (J/I).
7. Insert the pre-assembled seat and back with arms aggregation unit onto the gas lift to finish the assembly.

