



Special Notes:

DESIGN

Bellows: 2-ply 304 Stainless Steel
Tie Rods: Carbon Steel
Ends: 150 lb Carbon Steel
Misc.:
Temp: 700 Degrees F



GFM #	Size	Face to Face	BHC	Number Of Holes	Hole Size	Movement Ratings				Pressure @ 70 F	Weight
						Axial Comp	Axial Elong	Lateral	Vacuum		
PB-R-200	2	6.00	4.75"	4	0.75	0.9375	0.3125	0.375	Full	225	10.50
PB-R-250	2-1/2	6.00	5.50"	4	0.75	0.9375	0.3125	0.3125	Full	225	14.50
PB-R-300	3	6.00	6.00'	4	0.75	0.9375	0.2125	0.250	Full	225	16.50
PB-R-400	4	6.00	7.50"	8	0.75	0.9375	0.3125	0.1875	Full	225	26.00
PB-R-500	5	6.00	8.50"	8	0.875	0.9375	0.3125	0.1875	Full	225	32.00
PB-R-600	6	6.00	9.50"	8	0.875	0.9375	0.3125	0.125	Full	225	37.00
PB-R-800	8	6.00	11.75"	8	0.875	0.750	0.250	0.0937	Full	225	65.00
PB-R-1000	10	8.00	14.25"	12	1.00	1.25	0.375	0.125	Full	225	86.00
PB-R-1200	12	8.00	17.00"	12	1.00	1.25	0.375	0.125	Full	225	112.00