



Special Notes:

DESIGN

Bellows: 2-ply 304 Stainless Steel
Tie Rods: Carbon Steel
Ends: 150 lb Carbon Steel
Misc.:
Temp: 700 Degrees F



GFM #	Size	Face to Face	BHC	Number Of Holes	Hole Size	Movement Ratings				Pressure @ 70 F	Weight
						Axial Comp	Axial Elong	Lateral	Vacuum		
PB-200	2	4.375	4.75"	4	0.75	0.50	0.125	0.125	Full	225	10.50
PB-250	2-1/2	4.375	5.50"	4	0.75	0.50	0.125	0.125	Full	225	14.50
PB-300	3	4.625	6.00"	4	0.75	0.50	0.125	0.125	Full	225	16.50
PB-400	4	4.625	7.50"	8	0.75	0.50	0.125	0.125	Full	225	26.00
PB-500	5	4.875	8.50"	8	0.875	0.50	0.125	0.125	Full	225	32.00
PB-600	6	5.00	9.50"	8	0.875	0.50	0.125	0.125	Full	225	37.00
PB-800	8	5.875	11.75"	8	0.875	0.50	0.125	0.125	Full	225	65.00
PB-1000	10	6.625	14.25"	12	1.00	0.50	0.125	0.125	Full	225	86.00
PB-1200	12	6.625	17.00"	12	1.00	0.50	0.125	0.125	Full	225	112.00