



Special Notes: NSF-61 LOW LEAD COMPLIANT

DESIGN

- A) Tube: 321 Stainless Steel
- B) Braid: 304 Stainless Steel
- C) Ends: Carbon Steel ANSI 150
- Misc.:
- Temp: 750 Degrees F
- Axial: 0.0"
- Lateral: 0.75"
- Vacuum: Full



GFM Part Number	Size Inches	Overall Length	Flange OD	Bolt Hole Center	No Bolt Hole	Hole Size	WORKING PRESSURE		Weight Lbs
							70° F	250° F	
PFL-200	2.0	12.0"	6.0"	4.75"	4	0.750"	150	225	.879
PFL-250	2-1/2	12.0"	7.0"	5.50"	4	0.750"	150	225	1.130
PFL-300	3.0	12.0"	7.5"	6.00"	4	0.750"	150	225	1.380
PFL-400	4.0	12.0"	9.0"	7.50"	8	0.750"	150	225	1.630
PFL-500	5.0	18.0"	10.0"	8.50"	8	0.875"	150	225	2.130
PFL-600	6.0	18.0"	11.0"	9.50"	8	0.875"	150	225	2.630
PFL-800	8.0	22.0"	13.5"	11.75"	8	0.875"	150	225	3.130
PFL-1000	10.0	22.0"	16.0"	14.25"	12	1.00"	150	225	2.630