



Special Notes:

DESIGN

A) Tube 321 Stainless Steel
 B) Braid 304 Stainless Steel
 C) Ends: C/S Groove Ends
 D) Ends: C/S ANSI Plate Flange
 Temp: 750 Degrees F
 Axial: 0.0"
 Lateral: 0.125"



GFM Part Number	Size Inches	Over All Length	Flange OD	Bolt Hole Center	No Bolt Holes	Hole Size	WORKING PRESSURE		Weight
							AT 70F	AT 250F	
PGF-200	2.0	12.0"	6.0"	4.75"	4	0.750"	442	407	15.25
PGF-250	2-1/2	12.0"	7.0"	5.50"	4	0.750"	390	359	16.85
PGF-300	3.0	13.0"	7.5"	6.00"	4	0.750"	310	286	18.95
PGF-400	4.0	13.0"	9.0"	7.50"	8	0.750"	250	230	22.25
PGF-500	5.0	14.0"	10.0"	8.50"	8	0.875"	185	170	31.25
PGF-600	6.0	14.0"	11.0"	9.50"	8	0.875"	165	151	38.36
PGF-800	8.0	15.0"	13.5"	11.75"	8	0.875"	220	202	57.98
PGF-1000	10.0	16.0"	16.0"	14.25"	12	1.00"	175	161	79.26
PGF-1200	12.0	17.0"	19.0"	17.00"	12	1.00"	160	147	110.00