



Special Notes:

DESIGN

- Tube:** Butyl
- Cover:** Butyl
- Reinforcement:** Nylon Tire Cord
- Ends:** Duck/Rubber 150#
- Misc.:**
- Temp:** 160 Degrees F



GFM #	Size	Face to Face	BHC	Number Of Holes	Hole Size	Movement Ratings				Pressure @ 160 F	Weight
						Axial Comp	Axial Elong	Lateral	Angular		
REJM200BB-6.0	2	6.0	4.75"	4	0.75"	1.75"	0.75"	0.75"	35	200	
REJM250BB-6.0	2-1/2	6.0	5.50"	4	0.75"	1.75"	0.75"	0.75"	30	200	
REJM300BB-6.0	3	6.0	6.00"	4	0.75"	1.75"	0.75"	0.75"	30	200	
REJM400BB-6.0	4	6.0	7.50"	8	0.75"	1.75"	0.75"	0.75"	25	200	
REJM500BB-6.0	5	6.0	8.50"	8	0.875"	1.75"	0.75"	0.75"	25	200	
REJM600BB-6.0	6	6.0	9.50"	8	0.875"	1.75"	0.75"	1.00"	20	200	
REJM800BB-6.0	8	6.0	11.75"	8	0.875"	1.75"	0.75"	1.00"	20	180	
REJM1000BB-8.0	10	8.0	14.25"	12	1.00"	1.75"	0.75"	1.00"	15	180	
REJM1200BB-8.0	12	8.0	17.00"	12	1.00"	1.75"	0.75"	1.00"	15	180	