

Zoom Camera

ATC-HZ5518W-LP




- 1/1.8" Progressive Scan Global Shutter CMOS
- 216x AF Zoom(18x optical zoom, 12x digital zoom)
- 1080p 60/50/30/25fps
- Mechanical Day&Night
- True WDR
- 3D DNR, Defog
- UART RS232-TTL(Pelco-D, Pelco C, VISCA, Hitachi)

ATC-HZ5518W-LP



· Dimensions



Specifications

Image Sensor	1/1.8" Progressive Scan Global Shutter CMOS
Effective Pixels	3.19MP 2064(H) x 1544(V)
Video Output mode	LVDS / Parallel / CVBS
Max. Video Resolution	LVDS / Parallel :1080p@60(50fps)
Synchronization system	Internal / External Option
Min.Illumination	Day mode: 0.1(Lux(F1.5) Night mode: 0.05Lux(F1.5/ IR-cut filter on) DSS off, AGC45dB
S/N Rate	More than 55dB(AGC off, DSS off)
Lens	Type AF Optical zoom lens(DC Iris), IR Corrective
	Focal Length f=6.8~120mm
	F-value F=1.61(W)~4.13(T)
	Angle of View Horizontal 54.5°(W)~3.4°(T), Vertical 42.3°(W)~2.5°(T)
Zoom ratio	Optical 18x / Digital 12x
Focus Min.Working Distance	0.1m(Wide)/2.0m(Tele)~∞
Focus Control	Auto/Interval/One Push/Manual/Preset
AE mode	Auto/Shutter Priority/Iris Priority/AGC Priority/Manual
Brightness	0~14
Manual Shutter	1/1, 1/2, 1/4(3), 1/8(6), 1/15(12), 1/30(25), 1/60(50)~1/10000
Manual Iris	F1.6~F32, Close
Sense-up	Off~32fields
ETC	Spot AE, Slow AE
D&N Mode	Auto/Day(Color)/Night(BW)/External-H or L
White Balance	AUTO/One Push/Indoor/Outdoor/ATW/Manual
Image Freeze	Off/On
Image Flip	Off/Horizontal/Vertical/H+V(180°Flip)
Privacy Mask Zone	8 Zones/14 mask color selectable
Digital Image Stabilization	Yes
Motion Detection	4 Zones

D-WDR	Off/Low/Middle/High
WDR	Off/On, Adjustable(Level:0~29, Contrast:0~5, Bright:0~19)
BLC	Off/On, Area selectable
HLC	Off/On, Area selectable
AGC	Max.48dB
Sharpness	Adjustable(0~15)
3D-DNR	Off/Auto/Low/Middle/High
2D-DNR	Off/Auto/Low/Middle/High
Defog	Off/On/Auto
Preset Position	256 position Presets(Zoom,Focus), 16Memory Presets, Custom Preset
Language	English
UART	Remote RS232 TTL +5.0V(+3.3V compatible)
	Protocol VISCA/Pelco-D/Pelco-P/Hitachi: Automatic detection
	Baud rate 2400/4800/9600/19200/38400/57600/115200bps
UTC	-
Supply Voltage	12VDC(9V to 15VDC)
Power Consumption	Max.7.4W / Non-working zoom&focus 4.9W
Dimension(mm)	51x59x97.7mm
Weight	Approx.277g
Operating Temperature	-10°C~+50°C, Humidity(20~80%)
Storage Temperature	-20°C~+60°C, Humidity(20~95%)