

UNICARE X-MATT

Universal maintenance product that provides an extra protective layer to all types of MATTE floors. UNICARE X-MATT can also be used on laminate, LVT and on our matte waterborne finishes like FORTICO, ECOFIX PLUS & OCULTO PLUS. UNICARE X-MATT provides an extra protective film and hides micro-scratches, maintaining the original look of the floor. The extra matte protection ensures that the finishing layer is maintained longer and prevents dirt becoming ingrained.

- » Extra protection layer for all types of MATTE waterborne finishes.
- » Can also be used on laminate, LVT and matte varnished floors.
- » Hides micro-scratches and restores the original look of the floor.

TECHNICAL DATA

Product type

waterborne

Cleaning

Water

Mixing ratio

Use undiluted

Gloss level

Extra matte

PH

8

Packaging

6 x 750 ml

Coverage

60 - 80 m²/liter
650-850 sq.ft./L
2460 - 3220 sq.ft./gal

Drying times

1 hour at room temperature

Storage/transport

between 5°C and 25°C

Shelf life

12 months in the original and unopened packaging.

Disposal

Dispose of residue and empty packaging in accordance with local ordinances.



0,75L

PREPARATION

Ensure that the floor is clean before applying UNICARE X-MATT. To this end, you can first clean the wood with Ciranova® Hard floor Fresh. Apply the UNICARE X-MATT to a dry and grease-free surface.

APPLICATION

Use the UNICARE X-MATT undiluted. Apply the UNICARE X-MATT evenly with a microfiber cloth or mop, in the direction of the wood grain. If necessary, you can apply a second layer of UNICARE X-MATT after 1 hour.

CAUTION

+/- 1 hour, depending on the amount applied, the surrounding temperature, the humidity and ventilation.

MAINTENANCE

For regular maintenance of varnished floors and floors treated with UNICARE X-MATT, use Ciranova® Hard Floor Fresh. For removing old layers of UNICARE X-MATT, use Ciranova® Hard Floor Cleaner.