

### RMC RENEW

Rubio® Monocoat Renew is a ready-to-use product that refreshes, restores and protects surfaces treated with Rubio® Monocoat Oil Plus 2C. Rubio® Monocoat Renew is used when the surface feels too dry or rough, or when the finish has worn down due to heavy use. When the colour of the surface needs to be restored, we recommend a renovation with Rubio® Monocoat Oil Plus 2C, using the corresponding colour of the treated surface.

### PRODUCT INFORMATION

#### › Unique characteristics

- Brings the surface back to a freshly oiled state
- Restores the depth and vibrance of the colour
- Masks scratches in the surface as long as the surface is not damaged
- Universal use

#### › Technical characteristics

- Physical state: liquid
- Unit weight: ± 0,90
- Colour: opaque
- Odour: specific
- Flash point: > 90° C
- Density: 0,9 kg/L

#### › Packaging

Available in 100 ml bottles, 0,5 L and 1 L cans.

#### › Storage

The product can be stored for up to 12 months.  
Store in dry conditions and in the original packaging.

### APPLICATION INFORMATION

#### › Instructions

**STEP 1.** Eliminate dirt and dust from the floor.

**STEP 2.** Apply Rubio® Monocoat Renew on to the surface to be treated. Use a minimal amount of the product to prevent the floor from becoming sticky.

**STEP 3.** Allow the product to react for a couple of minutes.

**STEP 4.** Wipe dry with a cloth, paper towel, or buffer with white pad.

**STEP 5.** Perform a final wipe using an absorbing cloth, until the surface feels completely dry.

**STEP 6.** Continue working in zones that can be fully wiped dry within 10 to 15 minutes.

The surface can be walked on after 4 to 6 hours.

Complete curing takes place after 6 days.

Cleaning can begin after 6 days. Clean using Rubio® Monocoat Surface Care Spray or a soft cloth that is lightly damp with water. In order to guarantee a long lifespan and protection, the use of Rubio® Monocoat maintenance products is imperative.



**ATTENTION:**

Cloths, saturated with oil, may spontaneously combust. After usage, they need to be soaked in water before disposal.

› **Consumption**

1L = ± 100 m<sup>2</sup> (1000 ft<sup>2</sup>)

*These usages are merely indicative.*

*It is always recommended to make a sample in order to calculate the exact usage.*

Check the packaging and the safety data sheet for more details.

For our complete assortment of products for the protection and colouring of interior and exterior wood, please visit [www.specialhardwood.com](http://www.specialhardwood.com)

YOUR DISTRIBUTOR:



**THE ORIGINAL**  
IMPORTERS OF *Rubio*  
MONOCOAT

[WWW.SPECIALHARDWOOD.COM](http://WWW.SPECIALHARDWOOD.COM)  
[MONOCOAT@SPECIALHARDWOOD.COM](mailto:MONOCOAT@SPECIALHARDWOOD.COM)  
1-877-928-9663

**LIABILITY:** It is the user's responsibility to establish, through his own tests, whether the product is suitable for the chosen application. In no case can Muylle Facon NV be held liable for any consequential damage. The information above may be subject to changes, which will be published in the updated versions of the technical data sheet. We cannot be held liable for poor results due to causes that are not related to the quality of the product. This technical information has been drawn up based on the currently available information and knowledge. The most recent technical data sheets can be requested or are available on the website. **Date of TDS: 12/4/2019. Check the safety information before using the product.**



*Rubio*<sup>®</sup>  
**MONOCOAT**

MUYLLE  FACON

**Muylle Facon BVBA**  
Ambachtenstraat 58  
8870 Izegem (BELGIE)

Tel. +32 (0) 51 30 80 54  
Fax +32 (0) 51 30 99 78  
[info@muyllefacon.be](mailto:info@muyllefacon.be)

[www.rubiomonocoat.com](http://www.rubiomonocoat.com)