

RMC WOODFILLER QUICK

Rubio® Monocoat Woodfiller Quick is a one-component, shrink-proof putty in mixable powder form. This product guarantees quick curing and is applied on interior joinery. Rubio® Monocoat Woodfiller Quick can be sanded very easily. The product has an excellent ability to absorb any correspondent finishing colour from the Rubio® Monocoat range. Rubio® Monocoat Woodfiller Quick is environmentally friendly.

PRODUCT INFORMATION

› Specific characteristics

- Quick curing
- Shrink-proof
- Environmentally friendly
- Excellent colour absorption
- Easy sanding

› Technical specifications

- Physical state (20°C): powder
- Colour: light, medium or dark
- Odour: specific
- pH: 7
- Density: 2.4 g/cm³
- Solubility: mixable with water (20°C)
- Other data: hygroscopic product
- Humidity: 2% maximum

› Packaging

PVC barrel: 5 and 25 kg.

› Storage

The product can be stored up to 12 months. Store in dry conditions and in its original packaging.

APPLICATION INFORMATION

› Instructions

Mix 5 parts of Rubio® Monocoat Woodfiller Quick powder with 2 parts of water. The blend can be used immediately. The treated location can be sanded after 2 hours (20°C and 40% relative humidity). Rubio® Monocoat Woodfiller Quick may bulge slightly while drying.

Lifespan of the blend:

The product can be used for 35 minutes when preserved in a sealed pot and in an environmental temperature of 20°C.

› Cleaning of the tools

Used tools can be cleaned with water.



Check the packaging and the safety data sheet for more details.

For our complete assortment of products and machinery for the protection and colouring of interior and exterior wood, please visit www.specialhardwood.com

YOUR DISTRIBUTOR:



THE ORIGINAL
IMPORTERS OF *Rubio*
MONOCOAT

WWW.SPECIALHARDWOOD.COM
MONOCOAT@SPECIALHARDWOOD.COM
1-877-928-9663

LIABILITY: It is the user's responsibility to establish, through his own tests, whether the product is suitable for the chosen application. In no case can Muylle Facon NV be held liable for any consequential damage. The information above may be subject to changes, which will be published in the updated versions of the technical data sheet. We cannot be held liable for poor results due to causes that are not related to the quality of the product. This technical information has been drawn up based on the currently available information and knowledge. The most recent technical data sheets can be requested or are available on the website. **Date of TDS: 28/11/2018. Check the safety information before using the product.**



Rubio[®] MONOCOAT

MUYLLE  FACON

Muylle Facon BVBA
Ambachtenstraat 58
8870 Izegem (BELGIË)

Tel. +32 (0) 51 30 80 54
Fax +32 (0) 51 30 99 78
info@muyllefacon.be

www.rubiomonocoat.com