

# INSTALLATION GUIDE

## NEEDED TOOLS

Ladder, safety goggles, gloves tin snips, tape measure, cordless drill and screwdriver bit 1/4 6" long  
White color-matched 1/2 zip screws INCLUDED

## SAFETY

Use a stable ladder, Check the ladder before use, Use the proper ladder height, Use a ladder stabilizer, and Have a helper

By following these safety tips, you can ensure that you can install your micromesh gutter guard safely and effectively.

### 1) CLEAN YOUR GUTTERS:

Before installing gutter guards, it is important to clean your gutters to ensure they are free of debris and functioning properly. Remove debris,, Check for downspout leader clogs, Inspect the gutters for any signs of damage or leaks, and make any necessary repairs before installing the gutter guards. Inspect the hanger and nails. Check the spacing of hangers every 16"-24" inches

### 2) STRAIGHT RUNS

Work left to right as viewed from the ground. Lay micromesh completely flat over existing gutters with the front lips 4'ft panels lined up. Designed specifically to fit hidden hangers and nails, works with all hangers.

### OVERLAP SECTION

The Leaf4go DIY micromesh guard connection overlap section is the part of the gutter guard where two sections of the guard overlap each other. The micromesh overlap is typically around 1/2" inches and is designed to ensure a secure fit and prevent debris from entering the gutter system. The overlap section also helps to keep the gutter guard in place during heavy rain or windy conditions.

### 3) FOR INSIDE CORNER:

Extend the first piece all the way into the gutter from the right or left side; fasten the 3-4 screws into the gutters and lean opposite piece against it

### 4) FOR OUTSIDE CORNER:

Using a set square to measure, cut a 45-degree angle using a hand grinder or tin snip tool on the first piece. Repeat this step the second piece. Line up the angles to form the outside corner and zip screw to the gutter to secure in place

