NOTE: 22.5 MAX RAIL TO RAIL 12.5 MIN RAIL TO RAIL VENTING FRONT AND SIDES, TOP AND BOTTOM /HINGED/ REMOVABLE HINGED/ REMOVABLE PERFORATED DOOR SIDE DOORS A 888888888888888 MOUNTING 14.214 SIDE KEYED LOCK, FRONT AND SIDES **FRONT** LEFT/ RIGHT 17.812 3/8" SQUARE INSIDE RAIL 16.500 TO 22.500 _ **CAGE NUT** RAIL ADJUSTMENT 18.312 RAIL TO RAIL - SEE NOTE -19.636 MAX -23.500 23.500 UNLESS OTHERWISE SPECIFIED: NAME DIMENSIONS ARE IN INCHES **TOLERANCES:** DRAWN FRACTIONAL±1/8 ANGULAR: BEND ±1DEGREE CHECKED **6U LINIER WM FIXED** TWO PLACE DECIMAL ±.03 **WEB PRINT** ENG APPR. THREE PLACE DECIMAL ±.01 CABINET, PERFORATED Surface Area MFG APPR. **DOOR** Q.A. PROPRIETARY AND CONFIDENTIAL MATERIAL SIZE DWG. NO. **REV** THE INFORMATION CONTAINED IN THIS COMMENTS: DRAWING IS THE SOLE PROPERTY OF 3142-3-001-06 WP FINISH KENDALI HOWARD, ANY REPRODUCTION NEXT ASSY USED ON IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OFKENDALL HOWARD SCALE: 1:20 WEIGHT: 32.56 | SHEET 1 OF 2 IS STRICTLY PROHIBITED. APPLICATION DO NOT SCALE DRAWING

3

2

