



M077A-4431				Controller:		KBL
Volt (V)	Current (Amps)	Pin (W)	Speed (rpm)	Torque (N·m)	Pout (W)	Eff (%)
12.9	2.55	32.91	2651	0.082	22.64	68.79
12.9	2.644	34.11	2645	0.086	23.73	69.57
12.9	2.766	35.68	2641	0.091	25.06	70.24
12.89	2.99	38.53	2629	0.102	28.17	73.11
12.88	3.324	42.79	2612	0.12	32.82	76.70
12.86	3.847	49.46	2588	0.143	38.79	78.43
12.83	4.565	58.58	2554	0.179	47.83	81.65
12.8	5.438	69.63	2512	0.222	58.31	83.74
12.76	6.543	83.46	2462	0.251	64.64	77.45
12.71	7.812	99.3	2403	0.291	73.32	73.84
12.66	9.194	116.4	2346	0.359	88.26	75.82
12.61	10.85	136.7	2281	0.451	107.8	78.86
12.54	12.79	160.4	2209	0.554	128.2	79.93
12.47	14.75	183.9	2141	0.658	147.5	80.21
12.40	16.84	208.8	2073	0.767	166.6	79.79
12.33	18.92	233.2	2009	0.881	185.3	79.46
12.25	21.11	258.6	1947	0.979	199.7	77.22