



M099B-4170				Controller: FS50L		
Volt (v)	Current (amps)	Pin (w)	Speed (r/min)	Torque (N·m)	Pout (W)	Eff (%)
298.40	0.26	77.99	1999	0.06	11.7	15.01
298.40	0.28	82.15	1999	0.08	16.4	19.98
298.30	0.31	91.49	1999	0.14	28.9	31.56
298.40	0.39	117.30	2000	0.25	53.2	45.36
298.30	0.53	156.90	1999	0.45	93.3	59.45
298.30	0.69	207.00	1999	0.67	140.1	67.68
298.40	0.88	263.90	2000	0.93	195.2	73.97
298.30	1.09	324.80	1999	1.21	254.1	78.23
298.20	1.31	391.90	1999	1.51	315.6	80.53
298.30	1.56	466.60	1999	1.84	384.8	82.47
298.20	1.84	548.30	1999	2.20	460.7	84.02
298.30	2.14	637.30	1999	2.59	542.0	85.05
298.30	2.45	731.10	1999	2.99	626.7	85.72
298.20	2.80	834.90	1999	3.43	718.9	86.11
298.20	3.17	946.00	1999	3.90	815.5	86.21
298.20	3.56	1063.00	1999	4.38	917.1	86.27