



M099B-4436				Controller: KLS		
Volt (v)	Current (amps)	Pin (w)	Speed (r/min)	Torque (N·m)	Pout (W)	Eff (%)
48.65	2.337	113.7	2994	0.079	24.91	21.91
48.66	2.174	105.8	2999	0.095	29.91	28.27
48.65	2.329	113.3	2996	0.120	37.54	33.13
48.65	2.530	123.1	2999	0.167	52.51	42.66
48.63	2.991	145.4	3000	0.249	78.33	53.87
48.61	3.687	179.3	3001	0.342	107.6	60.01
48.59	4.451	216.3	2990	0.466	145.9	67.45
48.57	5.365	260.6	2965	0.620	192.6	73.91
48.53	6.668	323.6	2971	0.834	259.4	80.16
48.49	8.302	402.5	2982	1.041	325.0	80.75
48.44	10.02	485.3	2944	1.315	405.3	83.52
48.38	12.25	592.6	2936	1.620	498.0	84.04
48.31	14.72	711.0	2915	1.966	599.9	84.37
48.23	17.56	846.9	2895	2.393	725.2	85.63
48.14	20.79	1001	2854	2.857	853.9	85.30
48.05	23.91	1149	2844	3.330	991.6	86.30
47.96	27.11	1300	2791	3.785	1106	85.08
47.87	30.39	1454	2775	4.295	1248	85.83