



<b>M123C-4412</b>				<b>Controller:</b>		<b>KLS</b>
Volt (V)	Current (Amps)	Pin (W)	Speed (rpm)	Torque (N·m)	Pout (W)	Eff (%)
24.68	3.53	87.01	2449	0.05	13.78	15.84
24.66	3.64	89.81	2447	0.08	21.48	23.92
24.65	4.17	102.90	2445	0.14	35.60	34.60
24.63	4.98	122.70	2438	0.22	55.85	45.52
24.60	6.19	152.30	2431	0.33	84.55	55.52
24.55	7.73	189.90	2422	0.49	125.1	65.88
24.48	10.05	246.20	2410	0.70	176.0	71.49
24.42	12.39	302.40	2394	0.95	238.7	78.94
24.32	15.65	380.60	2378	1.24	309.0	81.19
24.24	18.60	450.70	2362	1.59	392.0	86.98
24.13	22.22	536.10	2345	1.92	471.8	88.01
24.03	25.70	617.50	2320	2.28	554.3	89.77
23.92	29.52	706.10	2296	2.68	643.2	91.09
23.81	33.59	799.70	2273	3.09	734.3	91.82
23.70	38.27	906.90	2254	3.52	829.4	91.45
23.60	42.54	1004.00	2233	3.97	928.4	92.47
23.49	47.09	1106.00	2214	4.42	1026	92.77
23.39	52.02	1217.00	2200	4.88	1125	92.44
23.28	57.22	1332.00	2184	5.43	1242	93.24
23.16	62.61	1450.00	2164	5.95	1347	92.90
23.05	68.28	1574.00	2145	6.51	1461	92.82
22.93	74.13	1700.00	2131	7.09	1581	93.00
22.81	79.83	1821.00	2115	7.57	1676	92.04
22.69	85.96	1950.00	2097	8.21	1803	92.46
22.57	92.14	2079.00	2077	8.79	1911	91.92