



M154C-6230N				Controller : FL		
Voltage (V)	Current (amps)	Pin (W)	Speed (rpm)	Torque (N·m)	Pout (W)	Eff. (%)
299.10	0.929	277.8	2399	0.202	50.75	18.27
299.20	1.028	307.7	2399	0.258	64.82	21.07
299.10	1.204	360.2	2399	0.439	110.3	30.62
299.10	1.569	469.4	2398	0.784	196.9	41.94
299.10	2.096	626.9	2399	1.377	345.9	55.18
299.30	2.762	826.6	2399	2.245	564	68.23
299.00	3.543	1060	2399	3.093	777.1	73.31
299.00	4.52	1351	2399	4.206	1057	78.21
299.00	5.55	1660	2399	5.354	1345	81.03
298.90	6.66	1989	2397	6.518	1636	82.26
298.90	8.16	2439	2399	8.177	2054	84.23
298.60	9.49	2835	2399	9.66	2427	85.60
298.80	10.74	3208	2399	11.03	2771	86.38
298.70	12.14	3626	2399	12.34	3100	85.50
298.70	13.53	4042	2398	13.95	3503	86.67
298.60	14.90	4449	2399	15.42	3874	87.08
298.60	16.30	4867	2400	16.92	4253	87.38
298.80	17.65	5274	2399	18.33	4605	87.32
298.40	19.22	5734	2399	19.79	4972	86.71