



M154C-6630				Controller : KLS		
Voltage (V)	Current (amps)	Pin (W)	Speed (rpm)	Torque (N·m)	Pout (W)	Eff. (%)
51.66	1.915	98.91	1433	0.033	5.022	5.08
51.50	2.211	113.8	1428	0.243	36.26	31.86
51.11	4.416	225.7	1415	0.934	138.4	61.32
50.58	7.620	385.4	1396	1.956	285.9	74.18
50.04	10.920	546.5	1374	3.205	461.2	84.39
49.54	14.890	737.8	1353	4.579	648.9	87.95
49.07	19.740	968.8	1333	6.215	867.3	89.52
48.70	24.78	1207	1313	7.965	1095	90.72
48.39	29.77	1441	1297	9.702	1318	91.46
48.10	34.55	1662	1279	11.31	1515	91.16
47.88	38.38	1838	1264	12.72	1684	91.62
47.75	40.44	1931	1257	13.46	1771	91.71
47.61	42.70	2033	1248	14.21	1858	91.39
47.49	44.63	2119	1240	14.9	1934	91.27
47.38	46.40	2198	1233	15.55	2007	91.31
47.29	47.80	2260	1226	16.14	2072	91.68
47.20	49.22	2323	1220	16.64	2126	91.52
47.13	50.38	2374	1217	17.08	2176	91.66
47.05	51.64	2430	1211	17.49	2218	91.28
46.98	52.65	2473	1207	17.87	2258	91.31
46.90	53.89	2528	1203	18.24	2298	90.90
46.85	54.65	2560	1200	18.58	2334	91.17
46.80	55.42	2594	1195	18.91	2368	91.29
46.74	56.48	2640	1191	19.23	2398	90.83
46.69	57.30	2675	1187	19.54	2430	90.84
46.64	58.00	2705	1184	19.84	2460	90.94
46.58	58.92	2745	1180	20.1	2485	90.53