



M154D-6608				Controller: KLS		
Voltage (V)	Current (amps)	Pin (W)	Speed (RPM)	Torque (Nm)	Pout (W)	Eff (%)
25.32	7.294	184.7	1928	0.061	12.26	6.64%
25.31	7.721	195.4	1925	0.124	24.93	12.76%
25.27	9.203	232.5	1918	0.317	63.7	27.40%
25.20	11.77	296.5	1909	0.639	127.8	43.10%
25.10	15.31	384.3	1896	10.83	215	55.95%
24.99	19.44	485.7	1882	1.603	315.9	65.04%
24.86	23.87	593.6	1867	2.166	423.5	71.34%
24.72	28.98	716.2	1850	2.791	540.8	75.51%
24.57	34.14	838.9	1834	3.458	664.2	79.18%
24.41	39.8	971.5	1817	4.177	794.8	81.81%
24.23	46.02	1115	1798	4.947	931.6	83.55%
24.03	53.29	1280	1778	5.814	1083	84.61%
23.87	60.94	1455	1760	6.75	1244	85.50%
23.71	68.51	1624	1742	7.682	1401	86.27%
23.52	77.04	1812	1726	8.66	1565	86.37%
23.35	85.21	1990	1708	9.627	1722	86.53%
13.16	94	2177	1691	10.63	1882	86.45%
22.98	102.2	2349	1672	11.66	2041	86.89%
22.80	111.1	2533	1653	12.69	2196	86.70%
22.62	119.3	2698	1634	13.69	2342	86.81%
22.42	128.3	2876	1616	14.67	2483	86.34%
22.24	136.6	3037	1598	15.66	2619	86.24%
22.06	145.5	3209	1582	16.59	2747	85.60%
21.86	153.1	3347	1546	17.49	2833	84.64%