



M154D-6618				Controller : KLS		
Voltage (V)	Current (amps)	Pin (W)	Speed (rpm)	Torque (N·m)	Pout (W)	Eff. (%)
48.55	2.701	131.2	1637	0.015	2.625	2.00
48.48	3.298	159.9	1636	0.081	13.96	8.73
48.45	3.768	182.6	1635	0.276	47.24	25.87
48.47	4.389	212.7	1633	0.606	103.6	48.71
48.40	6.634	321.1	1630	1.004	171.3	53.35
48.34	8.429	407.5	1624	1.470	249.9	61.33
48.30	9.831	474.8	1621	1.970	334.4	70.43
48.24	12.07	582.1	1615	2.553	431.8	74.18
48.17	14.53	700.2	1615	3.189	539.2	77.01
48.12	16.72	804.8	1610	3.874	653.1	81.15
48.03	19.69	945.5	1603	4.606	773.2	81.78
47.96	21.97	1054	1596	5.379	898.7	85.27
47.89	24.98	1196	1589	6.262	1042	87.12
47.80	28.03	1340	1584	7.212	1196	89.25
47.70	31.48	1501	1579	8.155	1348	89.81
47.62	34.80	1657	1572	9.101	1498	90.40
47.52	38.84	1846	1563	10.09	1651	89.44
47.45	41.83	1985	1557	11.07	1805	90.93
47.37	45.36	2149	1555	12.04	1961	91.25
47.28	49.52	2341	1550	13.00	2111	90.18
47.21	53.06	2505	1544	13.96	2258	90.14
47.16	55.38	2612	1537	14.91	2400	91.88
47.08	59.13	2784	1530	15.79	2530	90.88
47.05	61.46	2891	1527	16.66	2665	92.18
46.97	65.24	3065	1525	17.50	2794	91.16
46.93	67.43	3164	1521	18.28	2911	92.00
46.86	70.65	3310	1515	19.04	3021	91.27
46.84	72.20	3382	1511	19.76	3126	92.43