

# Hexagon Box - Direct

Architectural Surface / Suspended Luminaire



PROJECT:  TYPE:  DATE:

NOTES:



WHITE



BLACK



CUSTOM



Specification grade architectural round fixtures deliver minimalistic and distinctive lines that are able to endorse any design of hospitality, retail and commercial space.

- Available from 19" to 48" diameter
- Lumens from 2,125LM to 15,300LM
- Low profile housing 3.1" height
- Extruded aluminum housing
- 90+ CRI
- Suspended & surface mount

## ORDERING GUIDE Example: HEXBD-2440-40K-U-DM-90-WH-WH-SW

MODEL	SIZE/LUMENS	COLOUR TEMP.	VOLTAGE	DIMMING	CRI	FINISH	CANOPY FINISH
<b>HEXBD</b>	<b>1925</b> 19"   2,125LM	<b>27K</b> 2700K	<b>U</b> 120V-277V	<b>DM</b> 0-10V	<b>90</b> 90+ CRI	<b>WH</b> White	<b>WH</b> White
	<b>2440</b> 24"   3,400LM	<b>30K</b> 3000K	<b>UEB</b> 120V-277V W/ Emergency Backup			<b>BK</b> Black	<b>BK</b> Black
	<b>3690</b> 36"   7,650LM	<b>35K</b> 3500K				<b>Custom</b> Specify Ral#	<b>Custom</b> Specify Ral#
	<b>48180</b> 48"   15,300LM	<b>40K</b> 4000K				Example:	Example:
						<b>GR</b> Grey (RAL#9006)	<b>GR</b> Grey (RAL#9006)

## MOUNTING OPTION

**SW**  
Suspended wire

**SC**  
Suspended canopy

**SM**  
Surface mount

**Suspended Cable Length**  
ST- Standard 5ft (60" 1500mm)

**Suspended Power Cable Length**  
ST- Standard 5ft (60" 1500mm)

**Surface Mount Power Cable Length**  
ST- Standard 1ft (11.8" 300mm)

\*Phase dimming Triac/ELV: Available  
Please contact manufacture

# Hexagon Box - Direct

Architectural Surface / Suspended Luminaire



## SPECIFICATION

### Construction

Extruded aluminum housing  
Polycarbonate lens

### Electrical

0-10V dimming: 100%-10%  
Power factor >0.9  
Integral Driver Standard  
unless Remote Driver specified

### LED System

Available in 2700K, 3000K, 3500K, 4000K  
CRI 90+  
Sustainable LED modules

### Beam Angle

120°

### Emergency Battery

Optional Emergency output  
5 watts for 90 minutes

### Finish

Standard: Polyester powder coat white,  
black or custom finish (Specify RAL#)  
Example: Grey RAL#9006

### Environment

Suitable for dry or damp locations  
Indoor use only  
-20°C to 40°C (-4°F to 104°F)


### Certificates

ETL and cETL.  
Rated Lifetime of L70 50,000+ hrs


### Warranty

5 year limited parts warranty


## DIMENSIONS



## MOUNTING OPTIONS



**SW**  
Suspended wire



**SC**  
Suspended canopy



**SM**  
Surface mount

# Hexagon Box - Direct

Architectural Surface / Suspended Luminaire



## TECHNICAL INFORMATION

Model	Fixture Dimension (Dia x Width)		Total		# of Sections	Canopy Diameter (Suspended)	
	feet	inch	Lumens	Wattage		inch	mm
1925	1.6ft	18.9 x 3.1	2,125	25	1	9.8	250
2440	2ft	23.6 x 3.1	3,400	40	1	9.8	250
3690	3ft	35.4 x 3.1	7,650	90	1	9.8	250
48180	4ft	47.2 x 3.1	15,300	180	1	9.8	250

## DISTRIBUTION & OPTICAL

