

Linear - IP66 Direct 3.58"

Architectural Luminaire



PROJECT: TYPE: DATE:

NOTES:



Specification grade IP66 architectural LED fixtures are perfect for Natatorium applications and large spaces or structures exposed to nature's elements like airport or stadium exteriors, and transit stations.

- Salt spray anti-corrosion tested to IEC60068-2-11 standards
- PC frosted diffuser anti-UV, fire-protection rating 94-V2
- Pendant, Ceiling mount, Wall mount, Recessed Mounting
- Extruded aluminum housing
- Lumens from 4,900LM to 9,600LM
- Available from 48" to 96"
- 100 lumens per inch



ORDERING GUIDE Example: LL8989-4ft-40K-U-DM-85-GR-GR-PM

MODEL	SIZE/LUMENS	COLOUR TEMP.	VOLTAGE	DIMMING	CRI	FINISH	CANOPY FINISH
LL8989	4ft 48" 4,500LM	27K 2700K	U 120V-277V	DM 0-10V	85 85 CRI	GR Grey (RAL#9006)	GR Grey (RAL#9006)
	8ft 96" 9,000LM	30K 3000K	UEB 120V-277V W/ Emergency Backup		90 90+ CRI	WH White (RAL#9003)	WH White (RAL#9003)
	R-FT Continuous Rows	35K 3500K				BK Black (RAL#9004)	BK Black (RAL#9004)
	* Specify "FT" with length in feet	40K 4000K					

MOUNTING OPTION

PM
Pendant mount

CM
Ceiling mount

WM
Wall mount

RM
Recessed

Suspended Power Cable Length
ST- Standard 5ft (60" 1500mm)

Wall & Ceiling Mount Power Cable Length
ST- Standard 1ft (11.8" 300mm)

Linear - IP66 Direct 3.58"

Architectural Luminaire



SPECIFICATION

Construction

Extruded aluminum housing
Polycarbonate lens

Electrical

0-10V dimming: 100%-10%
Power factor >0.9
Integral Driver Standard

LED System

Available in 2700K, 3000K, 3500K, 4000K
CRI 85, CRI 90+ optional
Sustainable LED modules

Beam Angle

106°

Emergency Battery

Optional Emergency output
5 watts for 90 minutes

Finish

Standard: Polyester powder coat white,
black or Anodized silver

Environment

IP66
IK10
Salt spray tested to
IEC60068-2-11 standards
-30°C to 45°C (-22°F to 113°F)




Certificates

ETL and cETL.
Rated Lifetime of L70 50,000+ hrs


Warranty

5 year limited parts warranty

DIMENSIONS




MOUNTING OPTIONS




PM

Pendant mount




CM

Ceiling mount



WM

Wall mount



RM

Recessed

Pendant mount- G 3/4" Threaded Rod by others

Linear - IP66 Direct 3.58"

Architectural Luminaire







TECHNICAL INFORMATION

Size	Lumens	Wattage	lumen/W	lumen/ft	Watt/ft
4ft	4,900	45	109	1,225	11.25
8ft	9,800	90			

Testing on 4000K 85 CRI

DISTRIBUTION & OPTICAL



ACCESSORIES



IP66-PM
Pendant mount



IP66-CM
Ceiling mount



P66-WM
Wall mount



IP66-RM
Recessed



Continuous run



IP66-180
Continuous run



IP66-CH
Continuous run



P-M19-5-6FT