


Splash - Direct/Indirect

Architectural Surface / Suspended Luminaire



PROJECT: TYPE: DATE:

NOTES:



WHITE



BLACK



CUSTOM

Specification grade architectural round fixtures deliver minimalistic and distinctive lines that are able to endorse any design of hospitality, dealership and commercial space.

- Large varieties in sizes from 24" to 48"
- Lumens from 6,800LM to 18,700LM
- 5.5" height housing
- Extruded aluminum
- 90+ CRI
- Suspended & surface mount



ORDERING GUIDE Example: SPLDID-2440-40K-U-DM-90-WH-WH-SW

MODEL	SIZE/LUMENS	COLOUR TEMP.	VOLTAGE	DIMMING	CRI	FINISH	CANOPY FINISH
SPLDID	2460 24" 6,800LM	27K 2700K	U 120V-277V	DM 0-10V	90 90+ CRI	WH White	WH White
	36120 36" 10,200LM	30K 3000K	UEB 120V-277V W/ Emergency Backup	PD Phase dimming Triac/ELV		BK Black	BK Black
	48220 48" 18,700LM (Suspended)	35K 3500K				Custom Specify Ral#	Custom Specify Ral#
	48" 12,750LM (Surface Mount)	40K 4000K				Example:	Example:
	Custom					GR Grey (RAL#9006)	GR Grey (RAL#9006)

MOUNTING OPTION

SW
Suspended wire

SC
Suspended canopy

ST-24/ST-48/ST-60
Stem mount

SM
Surface mount

Suspended Cable Length
ST- Standard 60" (1524mm 5ft)

Suspended Power Cable Length
ST- Standard 60" (1524mm 5ft)

Stem Mount Stem Length
24" (610mm 2ft), 48" (1200mm 4ft), 60" (1500mm 5ft)
*Contact manufacturer for custom stem length

Surface Mount Power Cable Length
ST- Standard 12" (300mm 1ft)

*Phase dimming Triac/ELV: Available
Please contact manufacture

Splash - Direct/Indirect

Architectural Surface / Suspended Luminaire



SPECIFICATION

Construction

Extruded aluminum housing
Polycarbonate lens

Electrical

0-10V dimming: 100%-10%
Power factor >0.9
Integral Driver

LED System

Available in 2700K, 3000K, 3500K, 4000K
CRI 90+
Sustainable LED modules

Distribution

Indirect 33-40%
Direct 60-67%

Emergency Battery

Optional Emergency output
5 watts for 90 minutes

Finish

Standard: Polyester powder coat white,
black or custom finish (Specify RAL#)
Example: Grey RAL#9006

Environment

Suitable for dry or damp locations
Indoor use only
-20°C to 40°C (-4°F to 104°F)


Certificates

ETL and cETL.
Rated Lifetime of L70 50,000+ hrs

Warranty

5 year limited parts warranty

DIMENSIONS



MOUNTING OPTIONS




SW
Suspended wire



SC
Suspended canopy



ST
Stem mount



SM
Surface mount

Splash - Direct/Indirect

Architectural Surface / Suspended Luminaire



TECHNICAL INFORMATION

Suspended & Stem Mount

Model	Fixture Dimension (Dia x H)			Total		Indirect (Uplight)		Direct (Downlight)		Direct (Downlight) %	# of Sections	Suspension Points	# of Driver
	feet	inch	mm	Lumens	Wattage	Lumens	Wattage	Lumens	Wattage				
2460	2ft	23.6 x 5.5	600	6,800	80	2,550	30	4,250	50	63%	1	3	1
36120	3ft	35.4 x 5.5	900	10,200	120	4,080	48	6,120	72	60%	1	5	1
48220	4ft	47.2 x 5.5	1200	18,700	220	7,480	88	11,220	132	60%	1	5	2

Surface Mount

Model	Fixture Dimension (Dia x H)			Total		Indirect (Uplight)		Direct (Downlight)		Direct (Downlight) %	# of Sections	Suspension Points	# of Driver
	feet	inch	mm	Lumens	Wattage	Lumens	Wattage	Lumens	Wattage				
2460	2ft	23.6 x 6.9	600	6,800	80	2,550	30	4,250	50	63%	1	3	1
36120	3ft	35.4 x 6.9	900	10,200	120	4,080	48	6,120	72	60%	1	5	1
48220	4ft	47.2 x 6.9	1200	12,750	150	4,250	50	8,500	100	67%	1	5	2

DISTRIBUTION & OPTICAL

