

SAFETY DATA SHEET FOR COATZF DISSIPATIVE FLOOR FINISH

May be used to comply with ANSI Z400.1-2004, 29 CFR 1910.1200, Regulation (EC) No 1272/2008 (CLP Regulation), and GHS. Standard must be consulted for specific requirements.

SECTION 1: PRODUCT AND COMPANY INDENTIFICATION

Name of the Product: StaticWorx CoatZF Dissipative Floor Finish

Recommended Use: Antistatic Floor Finish

Producer: StaticWorx, Inc., 372 Hurricane Ln Suite 201, Williston, VT 05495

Telephone Number for Information: 617-923-2000

Emergency Phone Number: 800-255-3924 or Local Poison Control Center

SECTION 2: HAZARD(S) IDENTIFICATION

Classification: Reproductive toxicity, Category 2

Labelling: Symbol: Health Hazard

Signal Word: Warning

Suspected of damaging fertility or the unborn child. **Hazard Statement**: **Precautionary Statements:**

If exposed or concerned: Get medical advice/attention.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as required.

Store locked up.

Dispose of contents/container in compliance with all Federal, State/

Provincial and local laws and regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Weight % Component CAS# **Trade Secret** 120505MA106 0-1% Diethylene glycol monoethyl ether* 5-25% 111-90-0

SECTION 4: FIRST AID MEASURES

Skin Contact: Wash with soap and water. If irritation develops, get medical attention. Flush with water for at least 15 minutes. If irritation develops, get medical **Eye Contact:**

attention.

Ingestion: Drink several glasses of water. DO NOT induce vomiting. Contact a physician.

Inhalation: Move subject to fresh air.

^{*}This item is listed on the SARA Title III Section 313 Inventory



SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: The product is not flammable. Extinguish fire using media suitable for surrounding

Protective Equipment: Wear appropriate protective equipment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear impervious protective gloves and chemical splash proof eye glasses.

Contaminated surfaces will be extremely slippery.

Environmental Precautions: Keep spills and cleaning runoffs out of municipal sewers and open bodies of

water.

Absorb with sand or other absorbent material. Sweep up and shovel into **Methods For Cleaning Up:**

suitable containers for disposal. Dispose of the solids and the contaminated

absorbent material according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling: Use in well-ventilated areas; avoid breathing vapors. Keep containers closed when

not in use. Avoid contact with clothing, skin and eyes. Wash thoroughly after

handling. For commercial and industrial use only.

Storage Temperature: Max. 49°C/120°F-1°C/34°F

Keep from freezing-product may coagulate.

KEEP OUT OF REACH OF CHILDREN

Proper Storage:

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Component Value List Type

Diethylene Glycol Monoethyl Ether WEEL TWA 140 mg/m3 / 25 ppm

Appropriate Engineering Controls: Ventilation: Provide general and/or local exhaust ventilation to control

airborne levels below the exposure guidelines.

Individual Protection Measures:

Eye/Face Protection: Use safety glasses. Where contact with the material is likely, chemical goggles are

recommended because eye contact may cause discomfort even though it is

unlikely to cause injury.

No precautions other than clean body covering clothing should be needed. **Skin/Hand Protection:**

Atmospheric levels should be maintained below the exposure guideline. **Respiratory Protection:**

Use good personal hygiene. Do not consume or store food in the work area. Wash **Ingestion:**

hands before smoking or eating.



SECTION 9: PHYSICAL PROPERTIES

White liquid (dries clear) Appearance:

Odor: Polymer smell **Odor Threshold:** Not available

Physical State: Liquid pH: 7.0-8.0 **Melting Point at °C:** Not available

Boiling Point at °C: >200°F (100°C)

Flash Point (TCC): Not applicable. Product does not sustain combustion.

Evaporation Rate: Not available

Flammability (solid, gas): Classification according to EC-regulations "non-flammable".

Inflammability Limits (vol.% in air): Not available **Vapor Pressure (mmHg):** Not available Vapor Density (air=1): Not available

Specific Gravity (H20=1): 1.03

Solubility: Water soluble **Ignition Temperature:** Not available **Viscosity:** <10 cps (0.01 Pa•s) **Partition Coefficient:** Not available **Decomposition Temperature:** Not available

VOC: 0%*

SECTION 10: STABILITY AND REACTIVITY

This product is stable under normal conditions. **Chemical Stability: Conditions to Avoid:** Temperatures above 49°C/120°F and below 1°C/34°F.

Incompatible Materials: None known.

Hazardous Decomposition Products: Thermal decomposition may yield carbon oxides/hazardous organic products.

Hazardous Reactions: Product will not undergo hazardous polymerization.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity

Diethylene glycol monoethyl ether (111-90-0)

Ingestion: LD50, Rat 1,920-9,050 mg/kg

Skin Absorption: >8,400 mg/kg

Chronic Toxicity & Carcinogenicity: Did not cause cancer in lab animals.

Developmental Toxicity: Did not cause birth defects or any other fetal effects in lab animals.

Reproductive Toxicity: Studies in lab animals indicate that diethylene glycol monoethyl ether is not

a reproductive toxicant even when given in large amounts.

In vitro genetic toxicity studies were predominantly negative. Animal **Genetic Toxicology:**

genetic toxicity studies were negative.

^{*}Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Section 94508.



Trade Secret 120505MA106

LD50 (Oral - Rat): 710 mg/kg LC50 (Inhalation - Rat): 5.53 mg/L/4 hr > 2000 mg/kgLD50 (Dermal - Rat):

Target Organ Systemic Toxicity: Oral NOAEL 3.05 mg/kg; Inhalation NOAEL 0.00269

Skin-Rabbit: Irritating

Eye-Rabbit: Moderately Irritating Negative in Buehler Test **Skin Sensitization:**

Mutagenicity: Negative in in-vitro chromosome aberration test; Negative in Ames test

Toxicological Effects

Skin Contact: May cause mild skin irritation.

Skin Absorption: May be harmful if absorbed through the skin.

Eye Contact: May cause mild eye irritation.

Inhalation: May be harmful if inhaled. Material is irritating to mucous membranes and

upper respiratory tract.

Ingestion: May be harmful if swallowed.

SECTION 12: ECOLOGICAL INFORMATION

Diethylene glycol monoethyl ether (111-90-0)

MOVEMENT & PARTITIONING: Bioconcentration potential is low (BCF less than 100 or log Pow less than 3).

Potential for mobility in soil is very high (Koc between 0 and 50).

2.22E-8 atm*m3/mole; 25 °C Estimated. Henry's Law Constant (H):

Partition coefficient n-octanol/

water (log Pow): -0.54 Measured

Partition coefficient, soil organic

carbon/water (Koc): 20 Estimated

PERSISTENCE & DEGRADABILITY: Material is readily biodegradable. Passes OECD test(s) for ready

> biodegradability. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability. Indirect

Photodegradation with OH Radicals.

Rate Constant Atmospheric Half-life Method 4.093 h **Estimated** 3.14E-11 cm3/s

OECD Biodegradation Tests

Biodegradation **Exposure Time** Method

90 % 28 d OECD 301E Test > 90 % 5.5 d OECD 302B Test

Biological oxygen demand (BOD)

BOD 5 **BOD 10 BOD 20** 49 - 87 % 5 - 17 % 31 - 71 %

Chemical Oxygen Demand 1.84 mg/mg Theoretical Oxygen Demand 1.91 mg/mg



Ecotoxicity

Fish Acute & Prolonged Toxicity: LC50, bluegill (Lepomis 21,400 mg/l 96 h macrochirus). **Aquatic Invertebrate Acute Toxicity:** EC50, water flea Daphnia 3,940 - 4,670 mg/l 48 h magna.

EC10, bacteria 4,000 mg/l 16 h. **Toxicity to Micro-organisms:**

Trade Secret 120505MA106 ecotoxicity

Fish Acute & Prolonged Toxicity: LC50, (Rainbow trout) 158 mg/l 96 hr Aquatic Invertebrate Acute Toxicity: EC50, (Daphnia magna) 249 mg/l48 hr

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Methods: No special precautions. As packaged, if this product becomes waste it does not

meet the criteria of hazardous waste defined under the Resource Conservation and Recovery Act. Dispose of according to all Federal, state and local regulations.

SECTION 14: TRANSPORTATION INFORMATION

This product is not classified for transport under ADR/IMDG regulations.

SECTION 15: REGULATORY INFORMATION

Physical/Chemical Indication: Non-flammable.

Risk-phrase: (R36/38): irritates eyes and skin **Safety Phrase:** (S2): keep away from children, (S7): keep containers well closed,

(S24/25): avoid contact with skin and eyes,

(S62): if swallowed, do not induce vomiting; seek medical advice immediately and

show this container or label.

RIGHT TO KNOW (RTK)

| Ingredients | CAS# | MARTK | NJRTK | PARTK |
|-----------------------------------|-----------|-------|-------|-------|
| Water | 7732-18-5 | - | - | Χ |
| Diethylene glycol monoethyl ether | 111-90-0 | - | Χ | Χ |
| Tributoxyethyl phosphate | 78-51-3 | - | Χ | Χ |

The following components are defined as a "Hazardous Chemical" by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986 Sections 311, 312, 313.

Trade Secret 120505MA106:

International Inventories at CAS#

Level:

Diethylene Glycol Monoethyl Ether: Sections 311, 312, and 313, Delayed (Chronic) Health Hazard, Fire Hazard.

Sections 311 and 312, Immediate (Acute) Health Hazard.

All components of this product are listed on or exempt from the following

inventories: U.S.A (TSCA), Canada (DSL\NDSL).

This product is not subject to the reporting requirements under California's **California Proposition 65:**

Proposition 65.



EINECS Status: All components are included in the EINECS Inventories.

WHIMIS: This product has been classified according to the hazard criteria of the CPR and the

SDS contains all the information required by the CPR.

SECTION 16: OTHER INFORMATION

Special Hazard: N/A **NFPA RATING:**

Health 1

Flammability 0 Instability: 0

SDS Updated: 2015-04-08

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. Such information is to the best of the company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee of any kind, express or implied, is made as to its accuracy, reliability or completeness and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of use. It is the user's responsibility to satisfy himself as to the suitableness and completeness of such information for his own particular use.