



Mineral Guard Replacement Cartridge with Nature²[®] Technology[†]

[†]Nature² technology consists of the minerals silver and copper.

WARNING

FOR YOUR SAFETY – This product must be installed and serviced by a contractor who is licensed and qualified in pool equipment in accordance with the latest applicable version of AS3633, along with any other applicable local or council codes/standards. Before installing this product, read and follow all warning notices and instructions that accompany this product. Failure to follow warning notices and instructions may result in property damage, personal injury, or death. Improper installation and/or operation may void the warranty.



Improper installation and/or operation can create unwanted hazards which may cause serious injury, property damage, or death.

ATTENTION INSTALLER – This manual contains important information about the installation, operation and safe use of this product. This information should be given to the owner/operator of this equipment.

Section 1. Important Safety Instructions

READ AND FOLLOW ALL INSTRUCTIONS

WARNING

EQUIPMENT UNDER PRESSURE

Failure to heed the following can result in permanent injury or drowning.

Always turn pump off prior to installing or changing Mineral Guard cartridge. Your pump/filter system is operated under pressure and the pressure must be released before you begin work. Please see your pump/filter owner's manual for further instructions.

CAUTION

PRECAUTIONARY STATEMENT - HAZARDS TO HUMANS AND DOMESTIC ANIMALS

In the unlikely event that a cartridge breaks, mineral media should not be ingested by humans or animals as it may cause gastric distress.

FIRST AID IF INGESTED: Call poison control center or doctor immediately for treatment advice.

IMPORTANT NOTICE

HOMEOWNER BE AWARE: This product is not compatible with bromine based products, biguanide products or copper based algaecide and should not be used in any manner inconsistent with the product manuals and labeling.

SAVE THESE INSTRUCTIONS

Section 2. Installation and Use

2.1 Install the Cartridge

1. Install the cartridge into the Mineral Guard vessel.

NOTE: The unit can only be installed in one direction.

IMPORTANT
Initial superoxidation with chlorine is required to burn off contaminants and activate cartridge.

2. Increase your output to maximum or add additional chlorine to get free chlorine levels to around three (3) ppm.
3. Maintain this slightly elevated level of free chlorine for around 2 weeks.
4. You can now allow your pool sanitation to run at minimum allowable levels. (Australian Standards recommend one (1) ppm minimum residual chlorine.)

2.2 Cartridge Replacement Intervals

A cartridge lasts six (6) months or one season, whichever is shorter. The cartridge should not be used longer than six (6) continuous months.

2.3 Disposal

After six (6) months of use, discard cartridge in household trash. Do not save the cartridge for re-use. The cartridge is manufactured with the mineral media sealed inside. In the unlikely event that a cartridge breaks, remove it and vacuum out any media introduced into the pool.

Installation Date:	_____
Replacement Installation Date: (six months after your installation)	_____

Fluidra Group Australia Pty Ltd
1 Herbert Place, Smithfield NSW 2164
PO Box 7238 Wetherill Park NSW 1851, Australia
ABN: 87 002 641 965
AstralPool.com.au | 1300 186 875

Fluidra NZ Ltd
13 Douglas Alexander Parade
Rosedale Auckland 0632, New Zealand
NZBN: 942 903 181 70759
AstralPool.co.nz | 0800 807 665

A Fluidra Brand

©2023 ASTRALPOOL is a registered trademark of FLUIDRA COMMERCIAL, S.A.U., used under license. This document is subject to change without notice.

H0816500_REVB