

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006. SECTION 1: Identification of the substance/mixture and of the company/undertaking



1.1. Product identifier

SEAJET THINNER A

Product code: 908TR - Version 5 - Revision Date: 02-02-2022

1.2. Relevant identified uses of the substance or mixture and uses advised against

Paint and/or related product.

1.3. Details of the supplier of the safety data sheet

Chugoku Paints B.V., Sluisweg 12, 4794 SW Heijningen, Po Box 73, 4793 ZH Fijnaart, The Netherlands, Tel.+31-167-526100, E-mail: msdsregistration@cmpeurope.eu

1.4. Emergency telephone number

National Poisons Information Service: England & Wales / NHS dial 111, Scotland NHS 24, http://www.npis.org N.Ireland, Contact your local GP or pharmacist during normal hours, www.gpoutofhours.hscni.net for GP services Out-of-Hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 H226 Flammable liquid and vapour.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements



GHS02



GHS07



GHS08

Hazard pictogram(s):

Signal word: Danger

Labelling according to Regulation (EC) No 1272/2008 [CLP]:

Hazard statement(s):

H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.

H315 Causes skin irritation.
H319 Causes serious eye irritation.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Supplemental hazard information (EU): Not applicable.

Page 1/16 Issue Date: 27-6-2022





Product code: 908TR - Version 5 - Revision Date: 02-02-2022

Precautionary statement(s)

Prevention:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260: Do not breathe vapours/spray.

P280: Wear protective gloves, protective clothing, eye protection, face protection.

Response:

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331: Do NOT induce vomiting.

Storage & Disposal:

P501: Dispose of contents, container to a hazardous or special waste collection point.

Contains (EC 1272/2008 18.3(b)):

Reaction mass of Ethylbenzene and Xylene.

Extended details regarding health and environment, see Section 11 & 12.

2.3. Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Page 2/16 Issue Date: 27-6-2022





Product code: 908TR - Version 5 - Revision Date: 02-02-2022

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Substances presenting a health or environmental hazard within the meaning of Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List. (*) For full text of H-statements, see SECTION 16.

Substance name	Identification number		Hazard statement Co	` ' ` '
Reaction Mass Of Ethylbenzene And Xylene.	EG-nr: 905-588-0		H226 - Flam. Liq. 3	H319 - Eye Irrit. 2
	CAS-nr: -	95-100 %	H304 - Asp. Tox. 1	H332 - Acute Tox. 4
	Index: -		H312 - Acute Tox. 4	H335 - STOT SE 3
	Reach#: 01-2119488216-32	2	H315 - Skin Irrit. 2	H373 - STOT RE 2
 	\$ \$		SCL / M-factor / ATE: H312-ATE 1100	mg/kg bw, H332-ATE 29mg/l

Page 3/16 Issue Date: 27-6-2022





Product code: 908TR - Version 5 - Revision Date: 02-02-2022

SECTION 4: First aid measures

4.1. Description of first aid measures



Pay attention to your own safety! In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

following inhalation:



Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

following skin contact:



Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

following eye contact:



Remove contact lenses, if present and easy to do. Irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

following ingestion:



If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Potential acute symptoms and effects

following inhalation:

Exposure to vapours may cause a health hazard. Serious effects may be delayed following exposure.

Harmful if inhaled.

May cause respiratory irritation.

following skin contact:

Causes skin irritation. Harmful in contact with skin.

following eye contact:

Causes serious eye irritation.

following ingestion:

No known significant effects or critical hazards.

Potential delayed symptoms and effects

following inhalation:

No specific data.

following skin contact:

Adverse symptoms may include the following: irritation, redness

following eye contact:

Adverse symptoms may include the following: irritation, watering, redness

following ingestion:

No specific data.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

No specific treatment.

Page 4/16 Issue Date: 27-6-2022





Product code: 908TR - Version 5 - Revision Date: 02-02-2022

SECTION 5: Firefighting measures

5.1. Extinguishing media



Recommended: alcohol resistant foam, CO2, powders, water spray/mist.

Extinguishing media which must not be used for safety reasons:

Water jet. Zincdust containing products should not be extinguished with water.

5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. See Section 10.

5.3. Advice for firefighters

There is no one clothing material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Fire fighter's clothing conforming to European standard EN469 provides a basic level of protection for chemical incidents. Appropriate breathing apparatus may be required (Self-Contained Breathing Apparatus (SCBA)). Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Comply with company's emergency procedures. Exclude sources of ignition and ventilate the area. Use safety goggles or safety glasses, as well as any other appropriate personal protective equipment, at all times. Avoid breathing vapours. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Refer to protective measures listed in Sections 7 and 8.

For emergency responders: See Section 8 for information on appropriate personal protective equipment. See also the information: "For non-emergency personnel".

6.2. Environmental precautions

Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Place in a suitable container. Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. No sparking tools should be used. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Smoking, eating and drinking should be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses. Isolate from sources of heat, sparks and open flame.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

Information regarding fire and explosion hazard

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Page 5/16 Issue Date: 27-6-2022





Product code: 908TR - Version 5 - Revision Date: 02-02-2022

Notes on joint storage

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Additional information on storage conditions

Observe label precautions. Store between 0°C and 40°C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

Application: Thinning of paint (See also Technical Data Sheet.)

SECTION 8: Exposure controls/personal protection

8.1. Control pa	arameters
-----------------	-----------

Limits for occupational exposure and / or	(GB)	EU	
biological limit values	LIMIT VALUES TWA8h - STEL15 ppm-mg/m³	LIMIT VALUES TWA8h - STEL15 ppm-mg/m³	
Reaction Mass Of Ethylbenzene And Xylene.	TWA8h - ppm / - mg/m³	TWA8h - ppm / - mg/m³	
	STEL - ppm / - mg/m³	STEL15 - ppm / - mg/m³	
	Annotations -	Notation -	

U.K. - TWA=Time Weighted Average (8hr) - STEL=Short-term exposure limit (15-minute reference period) - H.S.E. Health and Safety Commission.

Europe - TWA = Time Weight Average (8hr) - Measured or calculated in relation to a reference period of 8 hours time-weighted average (TWA) - STEL = Short-term exposure limit - A limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified - SCOEL

Annotations / Notations:

BMGVs: Biological monitoring guidance values.

Carc: Capable of causing cancer and/or heritable genetic damage.

Inh.: Inhalable fraction. Resp.: Respirable fraction.

Sen: Capable of causing occupational asthma.

Sk: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

Skin: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin.

DNEL PNEC

DNEL - Not available. PNEC - Not available.

Page 6/16 Issue Date: 27-6-2022





Product code: 908TR - Version 5 - Revision Date: 02-02-2022

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Individual protection measures, such as personal protective equipment Personal Protection

Respiratory protection



If workers could be exposed to concentrations above the exposure limit they should use a respirator to EN 140, fitted with a filter suitable for both particulates and vapours to EN14387, with an assigned protection factor of at least 10 (e.g. A2P3).

Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Hand protection



There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. At repeated or prolonged contact; use gloves tested according to EN 374. Viton-gloves offer good protection for intense contact with most solvents, e.g. complete immersion in solvent.

Nitrile gloves offer good protection during spray application. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. The breakthrough time must be greater than the end use time of the product. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. USE PE gloves as under gloves for difficult situations like for instance: high exposure, unknown composition or unknown properties of the chemicals.

Gloves for repeated or prolonged exposure (Perm	neation breakthrough times > 480	min) - High Protection:
Material:	Minimum Thickness:	Chemical resistance:

Polyethylene (PE) Gloves0,062mmHighPVA Gloves0,2-0,3mmHighButyl Viton Gloves0,70mmHigh

Gloves for repeated or prolonged exposure (Permeation breakthrough times 240 - 480 min) - High Protection:

Material:Minimum Thickness:Chemical resistance:Polyethylene (PE) Gloves0,062mmHighPVA Gloves0,2-0,3mmHighButyl Viton Gloves0,70mmHigh

Gloves for repeated or prolonged exposure (Permeation breakthrough times 120-240 min) - Medium Protection:

Material:Minimum Thickness:Chemical resistance:Polyethylene (PE) Gloves0,062mmHighPVA Gloves0,2-0,3mmHighButyl Viton Gloves0,70mmHigh

Gloves for repeated or prolonged exposure (Permeation breakthrough times 60 - 120 min) - Medium Protection:

Material:Minimum Thickness:Chemical resistance:Polyethylene (PE) Gloves0,062mmHighPVA Gloves0,2-0,3mmHighButyl Viton Gloves0,70mmHigh

Page 7/16 Issue Date: 27-6-2022





Product code: 908TR - Version 5 - Revision Date: 02-02-2022

Gloves for short term exposure / splash protection (Permeation breakthrough times 30 - 60 min):

Material: Minimum Thickness: Chemical resistance:

Polyethylene (PE) Gloves0,062mmHighPVA Gloves0,2-0,3mmHighButyl Viton Gloves0,70mmHigh

Nitrile Gloves 0,31mm High

Gloves for short term exposure / splash protection (Permeation breakthrough times 10 - 30 min):

Minimum Thickness: Material: Chemical resistance: Polyethylene (PE) Gloves 0.062mm High **PVA Gloves** 0,2-0,3mm High **Butyl Viton Gloves** 0,70mm High **Butyl Gloves** 0,3mm High Neoprene Gloves <0.4mm High Nitrile Gloves 0,175mm High

Non suitable Gloves - non exhaustive list (Permeation breakthrough times < 10 min):

Material: Thickness (or less):

Natural Rubber Gloves 0,75mm
Nitrile Gloves -



Neoprene Gloves

Eye/face protection

Use safety eyewear tested according to EN 166 designed to protect against splash of liquids.



Skin protection

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

0,75mm



Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(a) Physical state

Liquid

(b) Colour

Colourless.

(c) Odour

Typical aromatic odour.

(d) Melting point/freezing point

Not applicable due to nature of the product.

(e) Boiling point or initial boiling point and boiling range

Not applicable due to nature of the product. Lowest Boiling Point: Reaction mass of Ethylbenzene and Xylene. - 135°C

(f) Flammability

Vapours are ignitable. See Flash point (h).

(g) Lower and upper explosion limit

The product itself is not explosive, but the formation of an explosive mixture of vapour or dust with air is possible.

Reaction Mass Of Ethylbenzene And Xylene.
1.0-7.0%

Page 8/16 Issue Date: 27-6-2022





Product code: 908TR - Version 5 - Revision Date: 02-02-2022

(h) Flash point

28°C - Method: ASTM D3278-96 (Re-appr.2004)

(i) Auto-ignition temperature

Not applicable due to nature of the product.

Lowest auto ignition temperature: Reaction mass of Ethylbenzene and Xylene. - 488°C

(j) Decomposition temperature

Not applicable due to nature of the product.

(k) pH

Not applicable due to nature of the product. Mixture is non-soluble (in water).

(I) Kinematic viscosity

0,0056 mm²/s @40°C - Method: ISO3219

Non-Newtonian liquid - thixotropic behaviour.

(m) Solubility

Not Soluble (in water).

(n) Partition coefficient n-octanol/water (log value)

Not applicable due to nature of the product.

(o) Vapour pressure

Reaction Mass Of Ethylbenzene And Xylene.
8.0 mbar

(p) Density and/or relative density

Relative density 0,87 @ 20°C - Method: ASTM D1475-98

(q) Relative vapour density

1-2 @ 20°C - Method: Calculated.

(r) Particle characteristics

Not applicable due to nature of the product.

9.2. Other information

Information with regard to physical hazard classes

No relevant information.

Other safety characteristics

No relevant information.

Page 9/16 Issue Date: 27-6-2022





Product code: 908TR - Version 5 - Revision Date: 02-02-2022

SECTION 10: Stability and reactivity

10.1. Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see Section 7).

10.3. Possibility of hazardous reactions

In combination with oxidizing agents, strongly alkaline and strongly acid materials, exothermic reactions and/or explosive reactions may occur or toxic vapours may arise.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials.

10.6. Hazardous decomposition products

Carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Substance name
Reaction Mass Of Ethylbenzene And Xylene LD50 Oral - >2000 mg/kg, Rat - LD50 Dermal - >2000 mg/kg, Rat - LC50 Inhalation - 29 mg/lRat,4h

Page 10/16 Issue Date: 27-6-2022





Product code: 908TR - Version 5 - Revision Date: 02-02-2022

Conclusion/Summary on mixture

Acute toxicity:

ATEmix (oral) : No specific data.
ATEmix (Dermal) : No specific data.
ATEmix (Inhalation) : No specific data.

Skin corrosion/irritation:

Conclusion/Summary on mixture: Causes skin irritation.

Method: Additivity approach, No testdata available.

Serious eye damage/irritation:

Conclusion/Summary on mixture: Causes serious eye irritation.

Method: Additivity approach, no testdata available.

Respiratory or skin sensitisation:

Conclusion/Summary on mixture

Respiratory sensitization Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

Skin sensitization Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

Germ cell mutagenicity:

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

Carcinogenicity:

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

Reproductive toxicity:

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

STOT - single exposure:

Conclusion/Summary on mixture: Based on available data, the classification criteria are not met. Justification: Concentration limit, No testdata available.

STOT - repeated exposure:

Conclusion/Summary on mixture: May cause damage to organs through prolonged or repeated exposure. Method: Concentration Limit, no testdata available.

Aspiration hazard:

Conclusion/Summary on mixture: May be fatal if swallowed and enters airways. Method: Additivity approach / Kinematic viscosity: 0,0056 mm²/s @40°C - Measured

Information on likely routes of exposure

Inhalation: No known significant effects or critical hazards.

Ingestion: No specific data.

Skin exposure: Causes skin irritation. Eye exposure: Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: Adverse symptoms may include the following: Cough

Ingestion: No specific data.

Skin exposure: Adverse symptoms may include the following: irritation, redness.

Eye exposure: Adverse symptoms may include the following: irritation, watering, redness.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure:

Potential immediate effects: No specific data. Potential delayed effects: No specific data.

Long term exposure:

Potential immediate effects: No specific data. Potential delayed effects: No specific data.

Page 11/16 Issue Date: 27-6-2022





Product code: 908TR - Version 5 - Revision Date: 02-02-2022

Potential chronic health effects:

Conclusion/Summary on mixture

General: No known significant effects or critical hazards.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

No known significant effects or critical hazards.

Other information: No relevant information.

11.2 Information on other hazards

Endocrine disrupting properties No relevant information.

Other information

No relevant information.

SECTION 12: Ecological information

There are no data available on the mixture itself. Do not allow to enter drains or water courses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified for eco-toxicological hazards.

12.1. Toxicity

Substance name - Species - Exposure - Results

Reaction Mass Of Ethylbenzene And Xylene. Acute (short-term) toxicity: Fish: LC50/96h - 2.6 mg/l, Crustacea: EC50/48h 1-10 mg/l (Daphnia magna),
Algae/aquatic plants: EC50/72h 2.2 mg/L (Pseudokirchneriella subcapitata), Other organisms: Not available. Chronic (long-term) toxicity: Fish: NOEC >1.3 mg/L
(Salmo gairdneri), Crustacea: NOEC 0.96mg/L, Algae/aquatic plants: NOEC 0.44mg/L, Other organisms: Not available.

Page 12/16 Issue Date: 27-6-2022





Product code: 908TR - Version 5 - Revision Date: 02-02-2022

1	12.2. Persistence and degradability
١	Substance name
Ī	Reaction Mass Of Ethylbenzene And Xylene Readily biodegradable.
:	
٠.	

12.3. Bioaccumulative potential

12.0. Bloaddanialative potential				
Substance name		og Kow	BCF	
Reaction Mass Of Ethylbenzene And Xylene.	<u>_</u>	3,1	25,9	<u></u>

12.4. Mobility in soil

Soil/water partition coefficient (KOC) : Not available.

Mobility : No relevant information.

12.5. Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6. Endocrine disrupting properties

No relevant information.

12.7. Other adverse effects

No relevant information.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product / Packaging disposal: Dispose of containers contaminated by the product in accordance with local or national legal provisions. The European Waste Catalogue (2000/532/EC) classification of this product. Waste codes / waste designations according to LoW: 08 01 11* Waste paint and varnish containing organic solvents or other hazardous substances. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority. Waste should not be disposed of by release to sewers. Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers.

Containers which are not properly cleaned may contain (highly) flammable or explosive vapours.

Special precautions: Use appropriate protective equipment for the removal and / or disposal of this product.

Page 13/16 Issue Date: 27-6-2022





Product code: 908TR - Version 5 - Revision Date: 02-02-2022

SECTION 14: Transport information

	ADR/RID/ADN	IMDG-Code	IATA
14.1. UN number or ID number 14.2. UN	UN 1263	UN 1263	UN 1263
14.2. UN	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
14.3. Transport hazard class(es)	3	3	3
Label(s)	3	3	
14.4. Packing group	<u> </u>		<u> </u>
14.5. Environmental hazards	No	No Marine Pollutant: No	No
Additional information	Hazard Identification Number No.: 30	Emergency Schedule Number (EmS): F-E, S-E	

14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The information in this Safety Data Sheet is required pursuant to

Annex II to regulation (EC) No 1907/2006 and its amendments.

The provisions of the Health and Safety at Work etc. Act [and the Control of Substances Hazardous to Health Regulations] apply to the use of this product at work.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

Page 14/16 Issue Date: 27-6-2022





Product code: 908TR - Version 5 - Revision Date: 02-02-2022

Seveso category (DIRECTIVE 2012/18/EU): P5c This product may add to the calculation for determining whether a site is within scope of the Seveso Directive on major accident hazards.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

H226	Measured
H312	Summation method (ATE)
H332	Summation method (ATE)
H315	Additivity approach
H319	Additivity approach
H304	Additivity approach
H335	Additivity approach

Concentration limit

Abbreviations and acronyms:

ADN : European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE : Acute Toxicity Estimate BCF : Bioconcentration factor

CLP : Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

DNEL : Derived No Effect Level

IATA : International Air Transport Association
IMDG- : International Maritime Dangerous Goods

Code

H373

Kow : octanol-water partition coefficient

LC50 : Lethal Concentration to 50 % of a test population

LD50 : Lethal Dose to 50% of a test population (Median Lethal Dose)

PBT : Persistent, Bioaccumulative and Toxic substance

PNEC : Predicted No Effect Concentration(s)

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STOT : Specific Target Organ Toxicity

vPvB : Very Persistent and Very Bioaccumulative

Page 15/16 Issue Date: 27-6-2022



H335

H373

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006. SEAJET THINNER A



Product code: 908TR - Version 5 - Revision Date: 02-02-2022

Full text of Hazard Statements appearing in Section 3.2.:

I dii toxt c	inazara otatemento appearing in ocotion of
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Amendments: 02-02-2022, §3,8,9,11,12&16

The information of this SDS is based on the present state of our knowledge and on current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

Page 16/16 Issue Date: 27-6-2022