



JNIVERSAL DIGITAL PRESSURE TESTER

Sykes-Pickavant.

Possible Applications



Fuel Low Pressure



acuum Pressure**





AdBlue Pressure



Oil Pressure*



Compression -Petrol / Diesel



Turbo Pressure



Cooling System



Particle Filter Pressure

UNIVERSAL AUTOMOTIVE PRESSURE TESTER

 st Adaptors required for entry via oil pressure sensor ** Additional transducer required

SAVE




Save, export, print & share results for specific applications

SENSORS

-1 TO 3BAR





Digital Kit Advantages:

- Easier to see smaller variations in pressure and
- Option to print results / evidence for reference or to present to customers
- Easier to read and provides more accurate readings than a traditional analogue gauge; which is essential for correct diagnosis on current models
- Suitable for high pressure petrol & diesel readings (with optional transducer & fittings)
- Unit pre-programmed for future add-on kits
- Compatible with previous and existing gauge products from Sykes-Pickavant



COMPREHENSIVE KIT

33100000



DIGITAL CONVERSION KIT

331000SP





Full Kit Contents:

- **Tester**
- Sensor 0 to 300Bars
- Sensor 1 > 3Bars
- **Universal Diesel Compression Adaptor**
- **Universal Petrol Compression Adaptor**
- Eight specific professional quick coupling adaptors
- Vacuum adaptors

Basic kit for use with existing Sykes-Pickavant products listed below

- Investment in current SP kits is not wasted due to backwards compatibility
- Includes Digital Multifunction Tester (tablet) & 331000-16 0-300 Bar Sensor with Cable

DIGITAL CONVERSION KIT - BACKWARDS COMPATIBILITY

The 331000SP can be used with the following Sykes-Pickavant kits

Cooling System Pressure

- 33159500 / V2 / V3 33186000*
- 33170000 / V2
- 33179500 / V2
- 33179600
- 33180000*

33189500*

33190000

33190500

- 33189000* 31420000 / V2 / V3
 - 31427500

Compression

31407500

- 31428000
 - 31428500 / V2
 - 31429500 / V2
- 31430000

Fuel Pressure

- 31461000 314860V2
- 314875V2 31468000
- 31469000 31489500
- 31480000 31492000
- 314800V2 314925V2

Oil Pressure

• 31470000 314700LG

*Requires 03176870 convertor

ACCESORIES

DIESEL HIGH PRESSURE KIT **33100100**

- Easily & safely test the diesel common rail pressure
- Safely test the diesel common rail pressure, both in line ("in series with engine running") and for direct pump pressure (cranking the engine)
- Instead of the pressure information provided by the car's sensor that may have an issue, this set provides all hardware (special sensor, plugs, hoses) to perform a precise and accurate test when used with the 33100000 or 331000SP Digital Pressure
- The hoses included in the set will allow measurement and diagnosis on most usual common rail engines

Includes;

- 2000bar Sensor
- Sensor Plug for direct pump pressure
- 2 x M12 x 150 Hoses for most common applications
- **Retrieving Reservoir**



DIESEL HIGH PRESSURE ADAPTORS

33100700

- When used with the 33100100 -Diesel High Pressure Kit, the diesel high pressure of most popular cars on the market can be tested (Delphi, Siemens, Bosch and Denso pumps)
- All adaptors feature an M12 x 150 thread to use with the pressure kit hoses and the others ends are as follows;
- M12x125 (2x)
- M14x150 (2x)
- M14x100 (1x)
- M16x100 (1x)










COMMON RAIL DUMMY REGULATOR SET

33100500


- This set, when used with 33100100, will allow bypass of the pump's regulator and measure the pressure to diagnose any regulator or pump issue
- After observing the weak pump pressure: Simply remove the regulator, and choose the right dummy plug to bypass and seal the port. If the pressure comes return to normal, the regulator causes the loss of pressure. If the pressure stays too low, the pump is defective. This test is recommended by



COMMON RAIL CAP SET \$\iiis 33100400

- When used with the 33100100, this set will allow closure of fuel inlet injectors directly on the common rail to identify whether an injector is leaking or not
- Works for 3, 4, 5 & 6 cylinder engines
- Includes 6 x M12x150 plugs & 6 x M14x150 plugs









PETROL HIGH PRESSURE ADAPTORS 33100300

 Using this kit alongside the 0-300bar sensor included in the 33100000, it's possible to test the High pressure of most popular Petrol engines (FSI, TFSI, TCe, T-Jet, etc.) by using the sensor location or the dedicated plug location

Kit includes the following adaptors:

- HP1 = M12x150
- HP2 = M12x125
- HP3 = M14x150
- HP4 = M10x100
- HP5 = M8x100







