



Revision 1 Dated: 21st October 2018 Doc no: FISDS065 Page 1 of 8

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier	
Product Name:	Clear Spray Grease
Product Code:	FSGCLEAR

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet	
Manufacturer:	Fortron International Limited
Address:	Unit 4 Cannel Road, Burntwood Business Park, Burntwood, Staffordshire, WS7 3FU
Country:	United Kingdom
Telephone:	01543 679 900
Fax:	01543 679 901

1.4 Emergency telephone number

01543 679 900 (office hours only)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture	
Classification under CLP:	Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; Lact.: H362; Skin Irrit. 2: H315; -: H229
Most important adverse effects:	Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. May cause harm to breast-fed children. Toxic to aquatic life with long lasting effects.

2.2 Label elements	
Hazard statements:	H222: Extremely flammable aerosol.
	H229: Pressurised container: May burst if heated
	H315: Causes skin irritation.
	H362: May cause harm to breast-fed children.
	H411: Toxic to aquatic life with long lasting effects.
Hazard Pictograms:	
	GHS02: GHS07 GHS09: Flame Exclamation Environmental Mark

Revision 1
Dated: 21st October 2018
Doc no: FISDS065
Page 2 of 8

Signal Words:	Danger
Precautionary statements:	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source. P251: Do not pierce or burn, even after use. P260: Do not breathe dust/fumes/gas/mist/vapours/spray. P263: Avoid contact during pregnancy/while nursing. P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

2.3 Other Hazards	
PBT:	This product is not identified as a PBT/vPvB substance.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures:

Hazardous Ingredients:

WHITE MINE	RAL OIL (PETROLEUM)			
EINECS	CAS	PBT / WEL	CLP Classification	Percent
232-455-8	8042-47-5	-	Asp. Tox. 1: H304	10-30%
REACH REGISTERED NUMBER(S): 01-2119487078-27				

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE				
EINECS	CAS	PBT / WEL	CLP Classification	Percent
921-024-6	-	-	Flam. Liq. 2: H225; Aquatic Chronic 2: H411; Skin Irrit. 2: H315; STOT SE 3: H336; Asp. Tox. 1: H304	10-30%
REACH REGISTERED NUMBER(S): 01-2119475514-35				

ALKANES, C1	4-17, CHLORO			
EINECS	CAS	PBT / WEL	CLP Classification	Percent
287-477-0	85535-85-9	-	Lact.: H362; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	5-10%

Non-classified ingredients:

PETROLEUM GASES, LIQUEFIED				
EINECS	CAS	PBT / WEL	CLP Classification	Percent
270-704-2	68476-85-7	-	Flam. Gas 1: H220; Press. Gas: H280	30-50%

Revision 1
Dated: 21st October 2018
Doc no: FISDS065
Page 3 of 8

4. FIRST AID MEASURES

4.1 Description of first aid measures		
Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.	
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.	
Ingestion:	Do not induce vomiting. Consult a doctor.	
Inhalation:	Move to fresh air in case of accidental inhalation of vapours.	

4.2 Most impo	4.2 Most important symptoms and effects, both acute and delayed		
Skin contact:	There may be irritation and redness at the site of contact.		
Eye contact:	There may be irritation and redness. The eyes may water profusely.		
Ingestion:	There may be soreness and redness of the mouth and throat.		
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing. Drowsiness or mental confusion may occur.		
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.		

4.3 Indication of any immediate medical attention and special treatment needed

Eye bathing equipment should be available on the premises.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media	
	Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2 Special hazards arising from the substance or mixture	
Exposure hazards:	In combustion emits toxic fumes.

5.3 Advice for fire-fighters	
Protective equipment:	Wear self-contained breathing apparatus.
	Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures	
Personal precautions:	Refer to section 8 of SDS for personal protection details.
	Eliminate all sources of ignition.

6.2 Environmental precautions	
Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.

Revision 1 Dated: 21st October 2018 Doc no: FISDS065 Page 4 of 8

6.3 Methods and material for containment and cleaning up		
Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.		
6.4 Reference to other sections		
Reference to other sections Refer to section 8 of SDS.		

7. HANDLING AND STORAGE

7.1 Precautions for safe handling	
Handling requirements	Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.
	Smoking is forbidden. Use non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities	
Storage conditions:	Store in a cool, well ventilated area. Keep container tightly closed.
Suitable packaging:	Not applicable.

7.3 Specific end use(s)	
No data available.	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parametersHazardous ingredients:

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

Workplace exposure limits: Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1200ppm	-	-	-

DNEL/PNEC Values	
DNEL / PNEC	No data available.

8.2 Exposure controls	
Engineering measures	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.
Respiratory protection	Self-contained breathing apparatus must be available in case of emergency.
Hand protection	Protective gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.
Environmental:	No special requirement.

Revision 1
Dated: 21st October 2018
Doc no: FISDS065
Page 5 of 8

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties		
State:	Aerosol	
Colour:	Off-white	
Odour:	Solvent	
Evaporation rate:	Fast	
Oxidising:	Not applicable.	
Solubility in water:	Insoluble	
Also soluble in:	Most organic solvents.	
Viscosity:	Non-viscous	
Boiling point/range°C:	<100	
Flammability limits %: lower:	No data available.	
upper:	No data available.	
Flash point°C:	-40	
Autoflammability°C:	No data available.	
Relative density:	Not applicable.	
VOC g/l:	No data available.	
Melting point/range°C:	No data available.	
Part.coeff. n-octanol/water:	No data available.	
Vapour pressure:	No data available.	
рН:	Not applicable.	

9.2. Other information	
Other information:	No data available.

10. STABILITY AND REACTIVITY

10.1 Reactivity	
Reactivity	Stable under recommended transport or storage conditions.
10.2 Chemical stability	
Chemical stability:	Stable under normal conditions.
10.3 Possibility of hazardous reaction	
Hazardous reactions	Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

Revision 1
Dated: 21st October 2018
Doc no: FISDS065
Page 6 of 8

10.4 Conditions to avoid		
Conditions to avoid	Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.	
10.5 Incompatible materials		
Materials to avoid	Strong oxidising agents. Strong acids.	
10.6 Hazardous decomposition products		
Haz. decomp. products:	In combustion emits toxic fumes.	

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

DERMAL	RAT	LD50	>2920	mg/kg
ORAL	RAT	LD50	>5840	mg/kg
VAPOURS	RAT	4H LC50	>25200	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact:	There may be irritation and redness at the site of contact.	
Eye contact:	There may be irritation and redness. The eyes may water profusely.	
Ingestion:	There may be soreness and redness of the mouth and throat.	
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing. Drowsiness or mental confusion may occur.	
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.	
Other information:	Not applicable.	

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Hazardous ingredients:

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

Daphnia magna	48H EC50	3	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	11.4	mg/l

12.2 Persistence and degradability	
Persistence and degradability:	No data available.

Revision 1
Dated: 21st October 2018
Doc no: FISDS065
Page 7 of 8

12.3 Bioaccumulative potential		
Bioaccumulative potential	No data available.	
12.4 Mobility in soil		
Mobility	Readily absorbed into soil. Highly volatile.	
12.5 Results of PBT and vPvB assessment		
PBT/vPvB identification:	This product is not identified as a PBT/vPvB substance.	
12.6 Other adverse effects		
Other adverse effects:	Toxic to aquatic organisms.	
13. DISPOSAL CONSIDERATIONS		
13.1 Waste treatment Methods		
Disposal operations recommendation:	Transfer to a suitable container and arrange for collection by specialised disposal company.	
NB:	The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.	
14. TRANSPORT INFORMATION		
14.1. UN number		
UN number:	UN1950	
14.2. UN proper shipping name		
Shipping name:	AEROSOLS	
14.3. Transport hazard class(es)		
Transport class:	2	
14.4. Packing group		
14.5. Environmental hazards		
Environmentally hazardous:	Yes Marine pollutant: No	
14.6. Special precautions for user		
Special precautions:	No special precautions.	
Tunnel code:	D	
Transport category:	2	
15. REGULATORY INFORMATION		

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture		
Specific regulations: Not applicable.		

15.2 Chemical safety assessment

Revision 1 Dated: 21st October 2018 Doc no: FISDS065 Page 8 of 8

16. OTHER INFORMATION

Other information		
Other information:	This safety data sheet is prepared in accordance with Commission	
	Regulation (EU) No 2015/830.	
Phrases used in s.2 and s.3:	H220: Extremely flammable gas.	
	H222: Extremely flammable aerosol.	
	H225: Highly flammable liquid and vapour.	
	H229: Pressurised container: May burst if heated	
	H304: May be fatal if swallowed and enters airways.	
	H315: Causes skin irritation.	
	H336: May cause drowsiness or dizziness.	
	H362: May cause harm to breast-fed children.	
	H410: Very toxic to aquatic life with long lasting effects.	
	H411: Toxic to aquatic life with long lasting effects.	
Legal disclaimer:	The above information is believed to be correct but does not purport to be	
	all inclusive and shall be used only as a guide. This company shall not be	
	held liable for any damage resulting from handling or from contact with	
	the above product.	

[FINAL PAGE]