
ULTIMATE

Paving Joint Compound

Universal









SAFG-4088





- Permeable : Min. joint: 3/16" Min. depth 7/8" *
- No mixing required / Ready to use
- 28 lbs Tub : yield 50-70 Sq.ft. *
- √ Fade / Weed / Frost Resistant
- ✓ Brush in, Water compaction, Air activated
- ✓ Natural stone, Pavers, Wetcast





APPLICATION IN ALL WEATHER CONDITIONS

855.967.1872

www.worldofstonesusa.com info@worldofstonesusa.com



Ultimate Application Guide

Visit www.worldofstonesusa.com to watch "How-to" Video.



Ultimate All-Weather Joint Compound



Soak the paving area, pour on the Ultimate joint compound.



2

Brush-in using broom, continue to wet down the Ultimate Joint Sand, fill joints completely.



3

Rinse area, remove excess material. Finish with pointing tool or as desired, Use soft brush to remove excess material.



* Ultimate Joint Compound coverage will vary depending on joint and product type; Wider joints will reduce coverage.

(*) Base type and bedding techniques must be free draining with zero movement base;

Designs vary such as use of hybrid base; plastic grids and/ or foam base materials. Bedding material may consist of hybrid system or open graded material (small coarse aggregate). Adhere to manufactures recommendation, guidelines, and local soil conditions. Do not clean with Muriatic Acid / No Limpiar con acido muriatico

and engagement.

Under no circumstances should a mechanical compactor be used directly on the slab surface.

Bajo ninguna circunstancia debera usarse la compactadora mecan/ca directamente sobre la superficie de la piedra.

