

GT-BU-G30

Great for garages, basements, utility rooms and more, this adjustable 2-panel LED bulb screws easily into a medium base E26 light socket. Fold the panels flat for down-lighting or tilt them up 90° AND rotate them 180° for specific light placement. Light coverage of approximately 15'x15' when installed at 10ft height with panels tilted at 45°*.

*This is an estimate. Multiple factors affect light coverage.

SPECS:

Brightness	3000 Lumen
Energy Used	30 Watts
Equivalent To	150W Incandescent
Energy Saved	80%
Power Source	E26 Base, 120V
Lifetime Hours	30,000
Lifetime Years	27.4 (3hr/day)
Color Temp CCT	5000K Daylight
Dimmable	No
Suitable For	Damp Locations
Size (WxHxD)	8.91" Dia. x 2.83" H
Item Weight	0.3 lbs
Certifications	Intertek FC
UPC	850040548938

3,000 LUMEN LED ADJUSTABLE 2-PANEL BULB

FEATURES

- New improved design is smaller and lighter while still efficient
- 2 adjustable panels pivot 90° up and down and rotate 180°
- 3X brighter than a standard incandescent bulb
- · Easy to install in garage, basement or shop
- · Fits standard light socket
- · For use in open sockets
- Omnidirectional light output
- Protective LED shield









©2023 GT Industrial Products