## **ROTARY THREAD®**

## RT1



### **Specifications**

Model Number	RT1
Thread Types	Inch, Metric, Pipe, SAE, National
Threads	· · · · · · · · · · · · · · · · · · ·
Works With	Dremel, Drill
Shank Size	1/8 inch (3.2 mm)
Head Diameter	3/8 inch (9 mm)
Overall Length	
Minimum Working ID	
Maximum Working OD	
Minimum Pitch	
Thread Angle	60 degrees
RPM	
Lube Recommend	Dry, Light Oil, or Mineral Spirits
PPE	, ,
Accessories	, , , , , , , , , , , , , , , , , , , ,

ID = Inner Diameter • OD = Outer Diameter • RPM = Revolutions Per Minute • Metric measurements are the most actual sizes, inch measurements shown are rounded with the exception of arbor diameter • Lube will help flush area and prolong tool life • Non-flammable lubes are recommended. • PPE = Personal Protective Equipment

For safety, usage instructions, tips, videos, demos, and warranty details see additional resources online.

WARNING: This product may including Lead and/or Nickel, which are classed as P65 Warning for the state of California. For more information: www.P65WARNINGS.ca.gov

www.rotarythread.com

PAT. US 10,183,372,B2









# **ROTARY THREAD**®

### Accessory

## RTC1

#### **Collet:**

1/8 inch to 1/4 inch collet 5/8 inch length



For safety, usage instructions, tips, videos, demos, and warranty details see additional resources online.

WARNING: This product may including Lead and/or Nickel, which are classed as P65 Warning for the state of California.
For more information: www.P65WARNINGS.ca.gov

www.rotary thread.com

PAT. US 10,183,372,B2

