



RT4



Specifications


| | |
|---------------------------------|------------------------------------|
| Model Number | RT4 |
| Thread Types | Inch, Metric, Pipe, SAE, National |
| Threads | Male (Bolt), Female (Nut) |
| Works With | Drill, Die Grinder |
| Shank Size | 1/4 inch (6.4 mm) |
| Head Diameter | 1-5/8 inch (40 mm) |
| Mandrel Used | RTM5 |
| Thickness | 0.118 inch (3 mm) |
| Minimum Working ID | 1-3/4 inch (42 mm) |
| Maximum Working OD | No Limit |
| Minimum Pitch | 28 TPI (0.8 metric) |
| Thread Angle | 60 degrees |
| RPM | Recommended 12,000 (Max 15,000) |
| Lube Recommend | Dry, Light Oil, or Mineral Spirits |
| PPE | Safety Glasses, Goggles, or Shield |
| Accessories | RTC1 |

ID = Inner Diameter • OD = Outer Diameter • RPM = Revolutions Per Minute • Metric measurements are the most actual sizes, inch measurements shown are rounded with the exception of arbor diameter • Lube will help flush area and prolong tool life • Non-flammable lubes are recommended. • PPE = Personal Protective Equipment

For safety, usage instructions, tips, videos, demos, and warranty details see additional resources online.

WARNING: This product may including Lead and/or Nickel, which are classed as P65 Warning for the state of California.
For more information: www.P65WARNINGS.ca.gov

www.rotarythread.com
PAT. US 10,183,372,B2



GRINDER / DRILL



WEAR SAFETY GOGGLES
USAR LENTES DE SEGURIDAD
PORTER DES LUNETTES DE SÉCURITÉ