



RT5B



Specifications


Model Number	RT5B
Thread Types	BUTTRESS Threads
Threads	Male (Bolt), Female (Nut)
Works With	Drill, Die Grinder
Shank Size	1/4 inch (6.4 mm)
Head Diameter	2 inch (50 mm)
Mandrel Used	RTM5
Thickness	0.315 inch (4 mm)
Minimum Working ID	2-1/8 inch (54 mm)
Maximum Working OD	No Limit
Minimum Pitch	NA
Thread Angle	7 x 45 degrees
RPM	Recommended 12,000 (Max 15,000)
Lube Recommend	Dry, Light Oil, or Mineral Spirits
PPE	Safety Glasses, Goggles, or Shield

ID = Inner Diameter • OD = Outer Diameter • RPM = Revolutions Per Minute • Metric measurements are the most actual sizes, inch measurements shown are rounded with the exception of arbor diameter • Lube will help flush area and prolong tool life • Non-flammable lubes are recommended. • PPE = Personal Protective Equipment

For safety, usage instructions, tips, videos, demos, and warranty details see additional resources online.

WARNING: This product may including Lead and/or Nickel, which are classed as P65 Warning for the state of California.
For more information: www.P65WARNINGS.ca.gov

www.rotarythread.com
PAT. US 10,183,372,B2



GRINDER / DRILL



WEAR SAFETY GOGGLES
USAR LENTES DE SEGURIDAD
PORTER DES LUNETTES DE SÉCURITÉ