

The 4-Piece Groove & Gland Kit



Great kit for touching up grooves, glands, or small areas which need to be cleaned up or dressed.



The RT3S1 was designed with a 25mm head diameter great for getting into 1 inch portals and hydraulic cylinder pistons and glands for cleaning up seal faces.

- 1) RT3S1
- **2** RTM3

ROTARY THREAD®

RT3S1



Specifications

Model Number	RT3S1
Profile Types	
Works With	Dremel, Drill, Die Grinder (when used with RTC1)
	1/8 inch (3.2 mm)
Head Diameter	
Mandrel Used	RTM3
Minimum Working ID	
Maximum Working OD	
Thickness of Disc	
Profile	Square
RPM	Recommended 12,000 (Max 15,000)
Lube Recommend	Dry, Light Oil, or Mineral Spirits
PPE	Safety Glasses, Goggles, or Shield
Accessories	RTC1

ID = Inner Diameter • OD = Outer Diameter • RPM = Revolutions Per Minute • Metric measurements are the most actual sizes, inch measurements shown are rounded with the exception of arbor diameter • Lube will help flush area and prolong tool life • Non-flammable lubes are recommended. • PPE = Personal Protective Equipment

For safety, usage instructions, tips, videos, demos, and warranty details see additional resources online.

WARNING: This product may including Lead and/or Nickel, which are classed as P65 Warning for the state of California.
For more information: www.P65WARNINGS.ca.gov

www.rotary thread.com

PAT. US 10,183,372,B2











RTM3

Mandrel:

0.236 inch (6 mm) Body Diameter \times 2 inches (51 mm) Long 1/8 inch (3.18 mm) Arbor Diameter

For safety, usage instructions, tips, videos, demos, and warranty details see additional resources online.

WARNING: This product may including Lead and/or Nickel, which are classed as P65 Warning for the state of California. For more information: www.P65WARNINGS.ca.gov

www.rotarythread.com PAT. US 10,183,372,B2



Connect with us today!







