

Release It

Liquid Release Agent

682

USE:

ICT Release It is a liquid release agent, used to keep mats and tools from sticking to the still wet concrete. *Release It* creates a barrier between the mat and the concrete surface, allowing a clean, non-staining, non-sticking surface. *Release It* may be used on all types of concrete surfaces but is designed primarily for stamped overlays. *Release It* can be used on interior and exterior surfaces. This clear formula will evaporate slowly and leave no residue.

DESCRIPTION:

Release It is a pleasant smelling liquid release agent which aids in breaking the bond between mats and concrete during the stamping process.

DIRECTIONS:

Using a pump sprayer, apply a generous amount of *Release It* to the still wet concrete. Spray the texture side of the mats, one time only before laying them on the surface to be stamped. Apply material to a small area (10—15 sq. ft) to ensure the best results. If used in too large of an area, the material may evaporate before the mats can be placed on the concrete which may result in a poor release and wasted material. *Release It* will slowly evaporate leaving little to no residue behind. *Release It* will cover approximately 250 sq. ft. per gallon.

LIMITATIONS:

Release It is formulated to be used with most texturing mats. However, test a little on texturing mats to insure compatibility before using. *ICT Release It* should only be used on the immediate area to be imprinted. If used on too large of an area at once, it will evaporate before the concrete can be textured. **DO NOT TROWEL OR, IN ANY WAY, MIX LIQUID RELEASE WITH SURFACE.** To make corrections, use the texturing mat and press out the unwanted impression.

PRECAUTIONS:

Never apply around heat sources (e.g., water heaters, furnaces, etc *Release It* is to be used by professionals and only in a well ventilated area. Wear eye protection when applying *ICT Release It*. Keep out of reach of children. Do not take internally. Please refer to the MSDS for further information and proper handling procedures.

PACKAGING:

1 and 5 gallon containers.

CHARACTERISTICS AND TECHNICAL DATA

<u>Liquid Properties</u>	<u>Test Results</u>
Weight/Gallon.....	6.7 lbs./gal.
Coverage/Gallon.....	Up to 250 sq. ft. per gal.
Shelf Life.....	2 years
Liters/gallon.....	3.875 liters

ICT Corporation

2410 McJunkin Road * Lakeland, FL 33803
(Nationwide): 888-296-5236 * (Local): 863-665-8787 * (Fax): 863-666-2768
(Email): info@innovativeconcrete.com
www.innovativeconcrete.com

All Innovative Concrete Technology Corp. products are manufactured with the finest raw materials. Shelf life is 24 months from the date of manufacturing when maintained in protected storage of 50°F to 90°F. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without warranty, express or implied, since conditions of use are beyond ICT's control. ICT Corp. disclaims any liability incurred in connection with the use of these data or suggestions.