

DATASHEET

CA054/FO / CA054N/FO

CA058/FO / CA058N/FO

Canterbury 13A Fused Connection Unit with Flex Outlet

www.thrion.co.uk



FINISH	Brushed Chrome, Grey Insert	Brushed Chrome, Black Insert	Matt Black, Black Insert	Brushed Chrome, White Insert	Black Nickel, Black Insert
PART CODE	CA054/FO 13A Fused Connection Unit+ Flex Outlet	CA054/FO BC/BK 13A Fused Connection Unit+ Flex Outlet	CA054/FO MB 13A Fused Connection Unit+ Flex Outlet	CA054/FO BC/W 13A Fused Connection Unit+ Flex Outlet	CA054/FO BN/BK 13A Fused Connection Unit+ Flex Outlet
DESCRIPTION	CA054N/FO 13A Fused Connection Unit + Neon+ Flex Outlet	CA054N/FO BC/BK 13A Fused Connection Unit + Neon+ Flex Outlet	CA054N/FO MB 13A Fused Connection Unit + Neon+ Flex Outlet	CA054N/FO BC/W 13A Fused Connection Unit + Neon+ Flex Outlet	CA054N/FO BN/BK 13A Fused Connection Unit + Neon+ Flex Outlet
MINIMUM MOUNTING DEPTH (MM)	25				
DIMENSIONS (MM)	Height: 86		Width: 86		Plate Thickness: 7
INPUT VOLTAGE	Mains 250V a.c.				
MAXIMUM LOAD (A)	13				
TERMINAL CAPACITY	3 x 2.5mm ² or 2 x 4mm ² or 1 x 6mm ²				
IP RATING	IP 20				
WARRANTY	25 years				
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes				
MANUFACTURED IN ACCORDANCE WITH	BS 1363-4				