

DATASHEET



CA054 / CA054N

CA058 / CA058N

Canterbury 13A Fused Connection Unit

www.thrion.co.uk



FINISH	Brushed Chrome, Grey Insert	Brushed Chrome, Black Insert	Matt Black, Black Insert	Brushed Chrome, White Insert	Black Nickel, Black Insert
PART CODE	CA054 13A Fused Connection Unit	CA054 BC/BK 13A Fused Connection Unit	CA054 MB 13A Fused Connection Unit	CA054 BC/W 13A Fused Connection Unit	CA054 BN/BK 13A Fused Connection Unit
	CA054N 13A Fused Connection Unit + Neon	CA054N BC/BK 13A Fused Connection Unit + Neon	CA054N MB 13A Fused Connection Unit + Neon	CA054N BC/W 13A Fused Connection Unit + Neon	CA054N BN/BK 13A Fused Connection Unit + Neon
DESCRIPTION	CA058 13A Switched Fused Connection Unit	CA058 BC/BK 13A Switched Fused Connection Unit	CA058 MB 13A Switched Fused Connection Unit	CA058 BC/W 13A Switched Fused Connection Unit	CA058 BN/BK 13A Switched Fused Connection Unit
	CA058N 13A Switched Fused Connection Unit + Neon	CA058N BC/BK 13A Switched Fused Connection Unit + Neon	CA058N MB 13A Switched Fused Connection Unit + Neon	CA058N BC/W 13A Switched Fused Connection Unit + Neon	CA058N BN/BK 13A Switched Fused Connection Unit + Neon
MINIMUM MOUNTING DEPTH (MM)	25				
DIMENSIONS (MM)	Height: 86		Width: 86		Plate Thickness: 7
INPUT VOLTAGE	Mains 250V a.c.				
MAXIMUM LOAD (A)	13				
TERMINAL CAPACITY	3 x 2.5mm ² or 2 x 4mm ² or 1 x 6mm ²				
IP RATING	IP 20				
WARRANTY	25 years				
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes				
MANUFACTURED IN ACCORDANCE WITH	BS 1363-4				